

# Package: TPMplt (via r-universe)

May 18, 2026

**Type** Package

**Title** Tool-Kit for Dynamic Materials Model and Thermal Processing Maps

**Version** 0.1.7

**Date** 2025-07-25

**Description** Provides a simple approach for constructing dynamic materials modeling suggested by Prasad and Gegel (1984) <[doi:10.1007/BF02664902](https://doi.org/10.1007/BF02664902)>. It can easily generate various processing-maps based on this model as well. The calculation result in this package contains full materials constants, information about power dissipation efficiency factor, and rheological properties, can be exported completely also, through which further analysis and customized plots will be applicable as well.

**License** GPL-3

**URL** <https://github.com/CubicZebra/TPMplt>

**BugReports** <https://github.com/CubicZebra/TPMplt/issues>

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.3

**Imports** VBTree, methods, ggplot2, metR, rgl, e1071, grDevices, graphics, stats, utils, RColorBrewer, dlm

**Depends** R (>= 2.10)

**Suggests** testthat, knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Chen Zhang [aut, cre, cph] (ORCID: <<https://orcid.org/0009-0007-7689-5030>>), Huakang Bian [ctb], Kenta Yamanaka [ths] (ORCID: <<https://orcid.org/0000-0003-1675-4731>>), Akihiko Chiba [ths]

**Maintainer** Chen Zhang <[chen.zhang\\_06sept@foxmail.com](mailto:chen.zhang_06sept@foxmail.com)>

**Config/pak/sysreqs** libabsl-dev cmake libfreetype6-dev libgdal-dev gdal-bin libgeos-dev libglu1-mesa-dev make texlive libicu-dev libpng-dev libuv1-dev libgl1-mesa-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev zlib1g-dev

**Repository** <https://cranhaven.r-universe.dev>

**Date/Publication** 2026-05-18 01:02:00 UTC

**RemoteUrl** <https://github.com/cranhaven/cranhaven.r-universe.dev>

**RemoteRef** package/TPMplt

**RemoteSha** 2b38e63e7ccd5e3f82a80002aa142ecbdb51f1e8

**RemoteSubdir** TPMplt

## Contents

Abstract-TPMplt . . . . .	2
API4TMZ . . . . .	3
DMMprocess . . . . .	4
epsExtract . . . . .	6
KFprocess . . . . .	7
lyIDdetector . . . . .	8
SSplots . . . . .	8
SVRModel . . . . .	9
T_get . . . . .	10
TCorrect . . . . .	11
TMZdatainput . . . . .	12
TPM2dplt . . . . .	13
TPM3dplt . . . . .	14
<b>Index</b>	<b>15</b>

---

Abstract-TPMplt      *Tool-Kit for Dynamic Materials Model and Thermal Processing Maps*

---

## Description

Provides a simple approach for constructing dynamic materials modeling (DMM) suggested by Prasad and Gegel. It can easily generate various processing-maps based on this model as well. The calculation result in this package contains full materials constants, information about power dissipation efficiency factor, and rheological properties, can be exported completely also, through which further analysis and customized plots will be applicable as well.

## Details

Input data should be of the data frame with "VBTree" style. Full calculation result returned from the function DMMprocess builds the dynamic material model. 2D and 3D thermal processing-maps can be generated based on this model. 2D plots are built using ggplot2 while 3D plots are constructed by rgl. Especially, 3D plots will separately generate two 3D surfaces, for power dissipation efficiency  $\eta$ , and rheological stability coefficient  $\xi$ , respectively.

**Author(s)**

Chen Zhang

Maintainer: Chen Zhang <chen.zhang\_06sept@foxmail.com>

**References**

Prasad, YVRK, Gegel, HL, Doraivelu, SM, Malas, JC, Morgan, JT, Lark, KA & Barker, DR (1984). Modeling of dynamic material behavior in hot deformation: forging of Ti-6242. Metallurgical Transactions A, 15, 1883-1892.

Prasad, YVRK, Rao, KP & Sasidhar, S (2015). Hot working guide: a compendium of processing maps. ASM international

**See Also**

[VBTree](#), [ggplot2](#), [rgl](#)

**Examples**

```
# Check the factors in column names of input data:
# Note: Temperature in layer2, Strain Rate in layer3.
require(VBTree)
vbt <- dl2vbt(chrvec2dl(colnames(TPMdata)))
vbt

# Export Strain Rate-Temperature table based on
# given strain condition (epsilon):
epstable <- epsExtract(TPMdata, 0.7, 2, 3)

# Build dynamic materials model (DMM) from Strain
# Rate-Temperature table:
DMM <- DMMprocess(epstable)

# Choose regression method for plots:
PLTbd <- SVRModel(DMM)

# 2D processing-map through selected regression method:
TPM2dplt(PLTbd)

# 3D processing-map through selected regression method:
TPM3dplt(PLTbd)
```

**Description**

Read data from multiple files with structured file names, then generate a summary table. It will also be available for the files from other tester apparatus by correct setting.

**Usage**

```
API4TMZ(Cd1, wd, ftype = ".csv", Straincln = 7, Stresscln = 8, startrow = 29)
```

**Arguments**

Cd1	An handmade double list to determine selected conditions.
wd	Work directory.
ftype	File type to be read. Default value is ".csv".
Straincln	An integer to specify column for Strain in your data. Default value is 7 means the 7th column contains strain data, in the files exported from Thermec Master-Z tester.
Stresscln	An integer to specify column for Strain in your data. Default value is 8 means the 8th column contains stress data, in the files exported from Thermec Master-Z tester.
startrow	An integer to ignore the prefix rows for testing conditions. Default value is 29.

**Value**

A matrix-like summary table for all input files.

**Examples**

```
variable1 <- c("factor11", "factor12", "factor13")
variable2 <- c("factor21", "factor22")
variable3 <- c("factor31", "factor32", "factor33", "factor34")
conditions <- list(variable1, variable2, variable3)

## Not run:
SummaryTable <- API4TMZ(conditions, "/Your_Data_Directory/")

## End(Not run)
```

---

DMMprocess

*Dynamic material modeling from strain rate temperature table*


---

**Description**

Dynamic material modeling based on strain rate-temperature table returned from the function [epsExtract](#). Material constants as well as power dissipation efficiency factors and rheological stability coefficients in current conditions will be returned.

**Usage**

```
DMMprocess(
  x,
  lgbase = 10,
  InteractMode = FALSE,
  ConsFunc = FALSE,
  legendcex = 0.65,
  legendloc = "bottomright"
)
```

**Arguments**

x	A strain rate-temperature table, returned from <a href="#">epsExtract</a> .
lgbase	A numeric value to specify the base of the logarithm calculations for processing map. The default value uses 10.
InteractMode	A boolean value to control figures' output and the printout of related constants during calculations. Default value FALSE means all fitting plots will not be outputted. If these outputs are necessary, set this parameter as TRUE then follow the prompt messages.
ConsFunc	A boolean value to determine whether calculating for constructive equation. The default value uses FALSE.
legendcex	A numeric value to determine the legend scale. It is activated only when the parameter InteractMode is TRUE. The default value is 0.65.
legendloc	A character object to determine the location of legend. It is activated only when the parameter InteractMode is TRUE. The default value is "bottomright".

**Value**

Serial material constants, constructive function, eta table and xi table through dynamic material model developed by Gegel and Prasad.

**See Also**

[VBTree](#), [epsExtract](#)

**Examples**

```
require(VBTree)
d12vbt(chrvec2dl(colnames(TPMdata)))
epstable <- epsExtract(TPMdata, 0.7, 2, 3)

# Without calculation for constitutive equation
DMM <- DMMprocess(epstable)
message(DMM)

# Calculating for constitutive equation but
# Without plots printout.
DMM <- DMMprocess(epstable, ConsFunc=TRUE)
```

```

message(DMM)

# Calculating for constitutive equation and
# required fitting plots printout. (message and selection in prompt)
## Not run:
DMMprocess(epstable, InteractMode=TRUE, ConsFunc=TRUE)

## End(Not run)

```

---

epsExtract

*Auto output for strain rate vs. temperature table*


---

## Description

Automatically output the strain rate vs. temperature table, by a specified strain condition.

## Usage

```
epsExtract(data, eps, lyT, lySR, manual = NULL)
```

## Arguments

data	A data frame with <a href="#">VBTree</a> style. Pay attention, all factors in column names should be separated by "-" symbol, and factors for temperatures and strain rates should be saved in pure numeric style.
eps	A numeric value to specify strain condition.
lyT	An integer to specify the layer for temperature attribute in the vector binary tree.
lySR	An integer to specify the layer for strain rate attribute in the vector binary tree.
manual	An integer vector with the length of 3 where the 1st element denotes the layer for Stress and Strain, the 2nd and 3rd elements represent the levels for Strain and Stress, respectively. The default setting is NULL, which can call the function <a href="#">lyIDdetector</a> for automatical completion this vector.

## Value

A list consist of a matrix table arranged by rows for strain rates while columns for temperatures, and a numeric value as strain condition for this strain rate-temperature table.

## See Also

[VBTree](#), [lyIDdetector](#)

## Examples

```

require(VBTree)
# Find locations for temperature and strain rate:
d12vbt(chrvec2dl(colnames(TPMdata)))
epsExtract(TPMdata, eps = 0.7, lyT = 2, lySR = 3)

```

---

KFprocess

*Enhanced Kalman filter to reduce the noise of raw data*

---

## Description

Kalman filter reducing the noise in raw data if it is necessary.

## Usage

```
KFprocess(x, manual = NULL, ...)
```

## Arguments

x	A data frame with <a href="#">VBTree</a> style. Pay attention, all factors in column names should be separated by "-" symbol, and factors for temperatures and strain rates should be saved in pure numeric style.
manual	An integer vector with the length of 3 where the 1st element denotes the layer for Stress and Strain, the 2nd and 3rd elements represent the levels for Strain and Stress, respectively. The default setting is NULL, which can call the function <a href="#">lyIDdetector</a> for automatic completion.
...	The arguments dV and dW passed on to <a href="#">dlmModPoly</a> in the function <a href="#">dlmSmooth</a> .

## Value

A data frame with the identical shape as input data, but with the smoothed stress values.

## See Also

[VBTree](#), [dlmModPoly](#), [dlmSmooth](#)

## Examples

```
# raw data without smoothing:
SSplots(TPMdata, 2, mfrow=c(2, 2))

# Smoothing to reduce the noise:
KFdt <-KFprocess(TPMdata, dV = 0.3, dW = 0.006)
SSplots(KFdt, 2, mfrow=c(2, 2))
```

lyIDdetector

*Detecting locations for Strain and Stress*

---

**Description**

Function for detecting the locations for Strain and Stress in data frame. It is an key component for automatic completion in the function of [epsExtract](#).

**Usage**

```
lyIDdetector(data, patterns = "[Ss][Tt][Rr]")
```

**Arguments**

data	A data frame with <a href="#">VBTree</a> style. Pay attention, all factors in column names should be separated by "-" symbol, and factors for temperatures and strain rates should be saved in pure numeric style.
patterns	A regex object to determine layer of Strain and Stress. The default pattern uses "[Ss][Tt][Rr]".

**Value**

A list consisted of the layer, and the levels in this layer for Strain and Stress respectively.

**See Also**

[VBTree](#), [TPMplt](#)

**Examples**

```
require(VBTree)
chrvec2dl(colnames(TPMdata))
lyIDdetector(TPMdata)
```

---

SSplots

*Automatic completion for Stress-Strain plots*

---

**Description**

Automatic completion for Stress-Strain plots

**Usage**

```
SSplots(x, grpby, manual = NULL, legendscale = 0.7, ...)
```

**Arguments**

x	A data frame with <a href="#">VBTree</a> style. Pay attention, all factors in column names should be separated by "-" symbol, and factors for temperatures and strain rates should be saved in pure numeric style.
grpby	Layer for variables to be grouped.
manual	A positive integer vector with length 3. The first value is layer for Stress and Strain, the second value is for Strain's level in this layer, and the third is Stress's level. Default setting is NULL, to call <a href="#">lyIDdetector</a> automatically fill this argument.
legendscale	A positive value to determine the scale of legend. Default value is 0.7
...	Arguments be passed to <a href="#">par</a> for plots arrangements. <code>mfrow</code> and <code>mfcoll</code> are recommended.

**Value**

Multiple Stress-Strain plots according to specified group methods.

**Examples**

```
require(VBTree)
# Find locations for temperature and strain rate:
# temperature in layer2, strain rate in layer3;
# Strain in layer1 level1, Stress in layer1 level2.
d12vbt(chrvec2dl(colnames(TPMdata)))

# Attention: Zoom your Plots panes large enough to ensure
# correct output!

# Plot multiple Stress-Strain curves, grouped by strain rate:
SSplots(TPMdata, 3, mfrow=c(3, 3))

# Plot multiple Stress-Strain curves, grouped by temperature:
SSplots(TPMdata, 2, mfrow=c(2, 2))

# Manual setting, for Stress-Strain plots:
SSplots(TPMdata, 2, manual=c(1, 1, 2), mfrow=c(2, 2))
```

---

SVRModel

*Build support vector regression result*


---

**Description**

Return a table with continuous values for eta and xi, based on prediction built by support vector regression model (SVR). The kernel function in SVR is radial basis.

**Usage**

```
SVRModel(x, seqby = 80)
```

**Arguments**

x	The calculation result returned from the function <a href="#">DMMprocess</a> .
seqby	A numeric value to specify the grid density. Default value is 80, namely the default mesh for original plot uses 80*80.

**Value**

A data frame including continuous values for eta and xi, calculated based on the discrete values for eta and xi returned from [DMMprocess](#). The strain condition in current calculation is also included.

**See Also**

[DMMprocess](#)

**Examples**

```
epstable <- epsExtract(TPMdata, 0.7, 2, 3)
DMM <- DMMprocess(epstable)
PLTbd <- SVRModel(DMM)
PLTbd
```

---

T\_get

*Calculating the adiabatic heating effect.*

---

**Description**

Calculating the adiabatic heating effect.

**Usage**

```
T_get(x, eta1, rho1, c1, ACorrect1 = 1, manual1 = NULL)
```

**Arguments**

x	A data frame with <a href="#">VBTree</a> style. Pay attention, all factors in column names should be separated by "-" symbol, and factors for temperatures and strain rates should be saved in pure numeric style.
eta1	Efficiency of deformation heating.
rho1	Density of materials, unit is g/cm <sup>3</sup> .
c1	Heat capacity of materials, unit is J/(kg*K).
ACorrect1	Coefficient to modify for density or heat capacity using different units. Default value is 1.
manual1	An integer vector with the length of 3 where the 1st element denotes the layer for Stress and Strain, the 2nd and 3rd elements represent the levels for Strain and Stress, respectively. The default setting is NULL, which can call the function <a href="#">lyIDDdetector</a> for automatical completion this vector.

**Value**

A data frame with the identical shape as input data. The values of stress was replaced by adiabatic heating effect.

**Examples**

```
# Constants of steels as example:
T_get(TPMdata, 0.9, 7.8, 502.416)
```

---

TCorrect	<i>Adiabatic heating effect correction</i>
----------	--

---

**Description**

Adiabatic heating effect correction

**Usage**

```
TCorrect(
  x,
  lyT,
  lySR,
  eta,
  rho,
  c,
  StrainSeq,
  ACorrect = 1,
  manual = NULL,
  Amplifier = 1000
)
```

**Arguments**

x	A data frame with <a href="#">VBTree</a> style. Pay attention, all factors in column names should be separated by "-" symbol, and factors for temperatures and strain rates should be saved in pure numeric style.
lyT	An integer to specify the layer for temperature attribute in the vector binary tree.
lySR	An integer to specify the layer for strain rate attribute in the vector binary tree.
eta	Efficiency of deformation heating.
rho	Density of materials, unit is g/cm <sup>3</sup> .
c	Heat capacity of materials, unit is J/(kg*K).
StrainSeq	A vector to specify the sequence for flow strain.
ACorrect	Coefficient to modify for density or heat capacity using different units. Default value is 1.

manual	An integer vector with the length of 3 where the 1st element denotes the layer for Stress and Strain, the 2nd and 3rd elements represent the levels for Strain and Stress, respectively. The default setting is NULL, which can call the function <a href="#">lyIDdetector</a> for automatical completion this vector.
Amplifier	Amplifier for linear fitting. Default value is 1000.

**Value**

A data frame with [VBTree](#) style including the adiabatic heating corrected flow stress using the StrainSeq as conditions.

**Examples**

```
# Constants of steels as example:
dt_TC <- TCorrect(TPMdata, 2, 3, 0.9, 7.8, 502.416, seq(0, 0.9, 0.005))

# Data without adiabatic heating correction
SSplots(TPMdata, 2, mfrow=c(2, 2))

# Data with adiabatic heating correction
SSplots(dt_TC, 2, mfrow=c(2, 2))
```

---

 TMZdatainput

---

*Read multiple files exported from Thermec Master-Z tester*


---

**Description**

Read data from multiple files with structured file names, then generate a summary data frame. It will also be available for the files from other tester apparatus by correct setting.

**Usage**

```
TMZdatainput(makeidx = FALSE, ...)
```

**Arguments**

makeidx	A boolean value to control the index column, inserted in the first column. Default setting is FALSE.
...	Arguments to be passed to <a href="#">API4TMZ</a> .

**Value**

A summary data frame for all input files.

**Examples**

```

variable1 <- c("factor11", "factor12", "factor13")
variable2 <- c("factor21", "factor22")
variable3 <- c("factor31", "factor32", "factor33", "factor34")
conditions <- list(variable1, variable2, variable3)

## Not run:
SummaryTable <- TMZdatainput(Cd1=conditions, wd="/Your_Data_Directory/")

## End(Not run)

```

---

TPM2dplt

*Plot 2d thermal process maps*


---

**Description**

Plot a 2d thermal process maps: logarithm strain rate as y axis while celsius temperature as x axis. Contours denotes the power dissipation efficiency factor, while the background with gradual colors represents rheological stability.

**Usage**

```
TPM2dplt(x, xloc = 0.09, yloc = 0.03, clrctrl = rev(rainbow(7))[-1])
```

**Arguments**

x	Regression results from modeling functions such as <a href="#">SVRModel</a> .
xloc	Location for annotatin in x axis. The default value is 0.09.
yloc	Location for annotatin in y axis. The default value is 0.03.
clrctrl	Colour vector to control eta background, the default value uses rainbow palette.

**Value**

A 2d thermal processing-map with logarithm strain rate as its y axis while celsius temperature as its x axis. Strain conditon is showed in top-left in the figure. Power dissipation efficiency factor eta is denoted by gradient blue contours, and the rheological stability coefficient are represented by gradient background.

**Examples**

```

epstable <- epsExtract(TPMdata, 0.7, 2, 3)
DMM <- DMMprocess(epstable)
PLTbd <- SVRModel(DMM)
TPM2dplt(PLTbd)

```

---

`TPM3dplt`*Plot 3d thermal processing-maps*

---

**Description**

Return a 3d thermal process result consisted of 3d surfaces for power dissipation efficiency eta and rheological stability coefficient xi respectively.

**Usage**

```
TPM3dplt(x, dvs = 5, etaclr = "heat", xiclcr = "cm")
```

**Arguments**

<code>x</code>	Regression results from modeling functions such as <a href="#">SVRModel</a> .
<code>dvs</code>	A positive integer to set the divisions for x, y and z labels in two 3d surface plots. The default value is 5.
<code>etaclr</code>	Colour control for eta. Optional value are "rainbow", "heat", "terrain", "topo" and "cm". "heat" is default value.
<code>xiclcr</code>	Colour control for xi. Optional value are "rainbow", "heat", "terrain", "topo" and "cm". "cm" is default value.

**Value**

Two 3d surface plots: the left one denotes power dissipation efficiency factor eta, while the right one is for rheological stability xi. A zero plane, z=0, for xi value is added in the right plots for determining unstable region.

**Examples**

```
epstable <- epsExtract(TPMdata, 0.7, 2, 3)
DMM <- DMMprocess(epstable)
PLTbd <- SVRModel(DMM)
TPM3dplt(PLTbd)
```

# Index

- \* **APIfunction**
    - API4TMZ, 3
    - TMZdatainput, 12
  - \* **DMMprocess**
    - DMMprocess, 4
  - \* **DMMresult**
    - DMMprocess, 4
  - \* **KFprocess**
    - KFprocess, 7
  - \* **PLTbuilder**
    - SVRModel, 9
    - TPM2dplt, 13
    - TPM3dplt, 14
  - \* **Processing-map**
    - TPM2dplt, 13
    - TPM3dplt, 14
  - \* **SR-T.table**
    - epsExtract, 6
  - \* **SSplots**
    - SSplots, 8
  - \* **SVRModel**
    - SVRModel, 9
  - \* **TCorrect**
    - TCorrect, 11
  - \* **epsExtract**
    - DMMprocess, 4
    - epsExtract, 6
    - lyIDdetector, 8
  - \* **internals**
    - T\_get, 10
  - \* **lyIDdetector**
    - epsExtract, 6
    - lyIDdetector, 8
    - SSplots, 8
- Abstract-TPMplt, 2  
API4TMZ, 3, 12
- d1mModPoly, 7  
d1mSmooth, 7
- DMMprocess, 4, 10
- epsExtract, 4, 5, 6, 8
- ggplot2, 3
- KFprocess, 7
- lyIDdetector, 6, 7, 8, 9, 10, 12
- par, 9
- rgl, 3
- SSplots, 8
- SVRModel, 9, 13, 14
- T\_get, 10
- TCorrect, 11
- TMZdatainput, 12
- TPM2dplt, 13
- TPM3dplt, 14
- TPMplt, 8
- VBTree, 3, 5–12