

Package: gradientPickerD3 (via r-universe)

March 24, 2025

Type Package

Title Interactive Color Gradient Picker Using 'htmlwidgets' and the Modified JS Script 'jquery-gradient-picker'

Version 0.1.0.0

Maintainer Christian D. Peikert

<christian.peikert@biologie.uni-freiburg.de>

Description Widget for an interactive selection and modification of a color gradient. 'gradientPickerD3' allows addition, removal and replacement of color ticks. List of numeric values will automatically translate in their corresponding tick position within the numeric range. App returns a data.frame containing tick values, colors and the positions in percent (0.0 to 1.0) for each color tick in the gradient. The original JS 'jquery-gradient-picker' was implemented by Matt Crinklaw-Vogt (nick: tantaman) <<https://github.com/tantaman/>>. Widget and JS modifications were done by CD. Peikert.

Depends R (>= 3.3.1)

Imports htmlwidgets, jsonlite, shiny

URL <https://github.com/peikert/gradientPickerD3>

BugReports <https://github.com/peikert/gradientPickerD3/issues>

LazyData true

Encoding UTF-8

License GPL-3

Collate 'gradientPickerD3.R' 'gradientPickerD3_example.R'

RoxygenNote 6.0.1

NeedsCompilation no

Author Christian D. Peikert [aut, cre]

Date/Publication 2017-09-15 11:56:09 UTC

Additional_repositories <https://cranhaven.r-universe.dev>

Config/pak/sysreqs make zlib1g-dev

Repository https://cranhaven.r-universe.dev

RemoteUrl https://github.com/cranhaven/cranhaven.r-universe.dev

RemoteRef package/gradientPickerD3

RemoteSha 9999d83d1f85055dd8e5a6a8df3dcebe2127feaa

RemoteSubdir gradientPickerD3

Contents

gradientPickerD3	2
gradientPickerD3-shiny	3
gradientPickerD3_example	4

Index	5
--------------	----------

gradientPickerD3	<i>gradientPickerD3</i>
------------------	-------------------------

Description

Creates a widget for an interactive selection and modification of a color gradient. `gradientPickerD3` allows the addition, removal and replacement of color ticks. List of numeric values will automatically translate in its corresponding tick position within the numeric range. App returns a R data.frame containing tick values, colors and the positions in percent (0.0 to 1.0) for each color tick in the gradient. The original JS 'jquery-gradient-picker' was implemented by Matt Crinklaw-Vogt. Widget and JS modifications were done by CD. Peikert.

Usage

```
gradientPickerD3(payload, width = NULL, height = NULL, elementId = NULL,
  border_extensions = 0.001, decimal_places = 8)
```

Arguments

<code>payload</code>	list containing 'ticks' and 'colors' to initialize the gradient. Ticks have to be numerical and in a logical order. Colors can be provided as R colors or HEX format.
<code>width, height</code>	must be a valid CSS unit (like '100%')
<code>elementId</code>	string id as a valid CSS element id
<code>border_extensions</code>	add to the min and max data range to cover the whole color spectrum
<code>decimal_places</code>	number of decimal places

Source

The interface was designed based on jquery-gradient-picker <https://github.com/tantaman/jquery-gradient-picker>, [htmlwidgets](#) and [shiny](#)

See Also

[gradientPickerD3_example](#)

Examples

```
ticks <- c(-1.8740103, -0.0040747, 1.4022244, 2.2177949, 3.2116766)
payload <- list(
  colors=c("purple", "blue", "green", "yellow", "red"),
  ticks=ticks
)
gradientPickerD3(payload)
```

gradientPickerD3-shiny

Shiny bindings for gradientPickerD3

Description

Output and render functions for using gradientPickerD3 within Shiny applications and interactive Rmd documents.

Usage

```
gradientPickerD3Output(outputId, width = "100%", height = "100%")
renderGradientPickerD3(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a gradientPickerD3
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

`gradientPickerD3_example`*gradientPickerD3_example*

Description

Creates an example shiny app which include the `gradientPickerD3` and a rendered table for `gradientPickerD3` return value. By clicking the reload button new random ticks will be generated.

Usage`gradientPickerD3_example()`

Index

gradientPickerD3, [2](#)
gradientPickerD3-shiny, [3](#)
gradientPickerD3_example, [3](#), [4](#)
gradientPickerD3Output
 ([gradientPickerD3-shiny](#)), [3](#)

htmlwidgets, [3](#)

renderGradientPickerD3
 ([gradientPickerD3-shiny](#)), [3](#)

shiny, [3](#)