Package: processpredictR (via r-universe)

November 11, 2026

Type Package

Title Process Prediction

Version 0.1.1

Description Means to predict process flow, such as process outcome, next activity, next time, remaining time, and remaining trace. Off-the-shelf predictive models based on the concept of Transformers are provided, as well as multiple way to customize the models. This package is partly based on work described in Zaharah A. Bukhsh, Aaqib Saeed, & Remco M. Dijkman. (2021). ``ProcessTransformer: Predictive Business Process Monitoring with Transformer Network" <doi:10.48550/arXiv.2104.00721>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

Imports bupaR, edeaR, eventdataR, dplyr, forcats, magrittr, reticulate, tidyr, tidyselect, purrr, stringr, keras, tensorflow, rlang, data.table, mltools, ggplot2, cli, glue, plotly

Config/testthat/edition 3

Depends R (>= 2.10)

Suggests knitr, rmarkdown, lubridate

VignetteBuilder knitr

NeedsCompilation no

Author Ivan Esin [aut], Gert Janssenswillen [cre], Hasselt University [cph]

Maintainer Gert Janssenswillen <gert.janssenswillen@uhasselt.be>

Config/pak/sysreqs cmake make libicu-dev libpng-dev libuv1-dev libssl-dev python3 zlib1g-dev

Repository https://cranhaven.r-universe.dev

Date/Publication 2026-11-11 03:03:00 UTC

RemoteUrl https://github.com/cranhaven/cranhaven.r-universe.dev

RemoteRef package/processpredictR

RemoteSha 9fdd2f15bd94d5691cf89efdb2755634c043c88f

RemoteSubdir processpredictR

Contents

confusion_matrix . . . 2
create_model . . . 3
create_vocabulary . . . 3
get_vocabulary . . . 4
max_case_length . . . 4
num_outputs . . . 5
plot.ppred_predictions . . . 5
ppred_examples_df . . . 6
ppred_model . . . 6
ppred_predictions . . . 6
prepare_examples . . . 6
print.ppred_model . . . 7
processpredictR . . . 8
split_train_test . . . 8
stack_layers . . . 9
tokenize . . . 9
vocab_size . . . 10

Index **11**

`confusion_matrix` *Confusion matrix for predictions*

Description

Confusion matrix for predictions

Usage

```
confusion_matrix(predictions, ...)
```

Arguments

`predictions`	`ppred_predictions`: A `data.frame` with predicted values returned by `predict.ppred_model()`.
`...`	additional arguments.

Value

A `table` object that can be used for plotting a confusion matrix using `plot()`.

create_model *Define transformer model*

Description

Defines the model using the keras functional API.

Usage

```
create_model(x_train, custom = FALSE, ...)
```

Arguments

x_train	data.frame: A processed data.frame from prepare_examples().
custom	logical (default FALSE): If TRUE, returns a custom model.
...	you can pass additional arguments to keras::keras_model() (ex.: name argument).

Value

A list containing a Transformer model (returned by keras::keras_model()) and some additional useful metrics.

create_vocabulary *Create a vocabulary*

Description

Creates a vocabulary of activities and outcome labels.

Usage

```
create_vocabulary(processed_df)
```

Arguments

processed_df	A preprocessed object of type ppred_examples_df returned by prepare_examples().

Value

A list consisting of:

- "keys_x": list of activity labels
- "keys_y": list of outcome labels (none for tasks "next_time" and "remaining_time")

get_vocabulary *Utils*

Description

Utils

Usage

```
get_vocabulary(examples)
```

Arguments

examples	a preprocessed dataset returned by prepare_examples_dt().

max_case_length *Calculate the maximum length of a case / number of activities in the longest trace in an event log*

Description

Calculate the maximum length of a case / number of activities in the longest trace in an event log

Usage

```
max_case_length(processed_df)
```

Arguments

processed_df	A processed dataset of class ppred_examples_df returned by prepare_examples().

Value

An integer number of the maximum case length (longest trace) in an event log.

Examples

```
library(processpredictR)
library(eventdataR)

df <- prepare_examples(patients)
max_case_length(df)
```

num_outputs *Calculate number of outputs (target variables)*

Description

Calculate number of outputs (target variables)

Usage

```
num_outputs(processed_df)
```

Arguments

processed_df	A processed dataset of class ppred_examples_df.

Value

an integer number of outputs for supplying as an argument to a Transformer model, i.e. number of unique labels for a specific process monitoring task.

Examples

```
library(processpredictR)
library(eventdataR)
df <- prepare_examples(patients)
num_outputs(df)
```

plot.ppred_predictions *Plot Methods*

Description

Visualize metric

Usage

```
## S3 method for class 'ppred_predictions'
plot(x, ...)
```

Arguments

x	Data to plot. An object of type ppred_predictions.
...	Additional variables

Value

A ggplot object, which can be customized further, if deemed necessary.

`ppred_examples_df` *ppred_examples_df object*

Description

object of type `pprep_examples_df` is a transformed event log returned by `prepare_examples_dt()`.

`ppred_model` *ppred_model object*

Description

object of type `pprep_model` is a list returned by processpredictR::create_model() containing a custom keras functional (transformer) model and some other useful metrics of an event log.

`ppred_predictions` *ppred_predictions object*

Description

object of type `pprep_predictions` is a data.frame with predicted values returned by predict.ppred_model().

`prepare_examples` *Convert a dataset of type `log` into a preprocessed format.*

Description

an event log is converted into a tibble where each row contains a cumulative sequence of activities per case. This sequence will eventually be feeded to the Transformer model's token embedding layer.

Usage

```
prepare_examples(
  log,
  task = c("outcome", "next_activity", "next_time", "remaining_time", "remaining_trace"),
  features = NULL,
  ...
)
```

Arguments

log	log: Object of class log or derivatives (grouped_log, eventlog, activitylog, etc.).
task	character: a process monitoring task for which to prepare an event log.
features	character (default NULL): additional features. Appends attributes (if present) numeric_features and/or categorical_features to a preprocessed event log.
...	additional arguments.

Value

a preprocessed dataset of class ppred_examples_df.

Examples

```
library(processpredictR)
library(eventdataR)

prepare_examples(patients, "next_activity")
```

---

print.ppred_model *Print methods*

Description

Print methods

Usage

```
## S3 method for class 'ppred_model'
print(x, ...)
```

Arguments

x	ppred_model: An object of class ppred_model.
...	Additional Arguments.

Value

prints a Transformer model from a list returned by create_model().

processpredictR *processpredictR*

Description

Means to predict process flow, such as process outcome, next activity, next time, remaining time, and remaining trace. Off-the-shelf predictive models based on the concept of Transformers are provided, as well as multiple way to customize the models. This package is partly based on work described in Zaharah A. Bukhsh, Aaqib Saeed, & Remco M. Dijkman. (2021). "ProcessTransformer: Predictive Business Process Monitoring with Transformer Network" doi:10.48550/arXiv.2104.00721.

Author(s)

Maintainer: Gert Janssenswillen <gert.janssenswillen@uhasselt.be>

Authors:

- Ivan Esin <ivan.esin@student.uhasselt>

Other contributors:

- Hasselt University [copyright holder]

split_train_test *Splits the preprocessed* data.frame.

Description

Returns train- and test dataframes as a list.

Usage

```
split_train_test(processed_df, split = 0.7)
```

Arguments

processed_df	A preprocessed object of type ppred_examples_df returned by prepare_examples().
split	numeric (default 0.7): A train-test split ratio.

Value

A list containing the train- and the test set objects.

Examples

```
library(processpredictR)
library(eventdataR)

df <- prepare_examples(patients, "next_activity")
split_train_test(df, split = 0.8)
```

`stack_layers` *Stacks a keras layer on top of existing model*

Description

User friendly interface to add a keras layer on top of existing model.

Usage

```
stack_layers(object, ...)
```

Arguments

`object`	a `list` containing a model returned by `create_model()`.
`...`	functions for adding layers by using functional keras API. For example, `keras::layer_dense(units=32 activation="relu")`.

Value

a `list` containing an adapted Transformer model.

`tokenize` *Tokenize features and target of a processed dataset of class* `ppred_examples_df`

Description

Tokenize features and target of a processed `ppred_examples_df` object to fit the Transformer model.

Usage

```
tokenize(processed_df)
```

Arguments

`processed_df`	A preprocessed object of type `ppred_examples_df` returned by `prepare_examples()`.

Value

A list of (sequence) tokens and additional numeric or categorical features.

---

vocab_size *Calculate the vocabulary size, i.e. the sum of number of activities, outcome labels and padding keys*

Description

Calculate the vocabulary size, i.e. the sum of number of activities, outcome labels and padding keys

Usage

```
vocab_size(processed_df)
```

Arguments

processed_df	A processed dataset of class ppred_examples_df from prepare_examples().

Value

an integer number of vocabulary size to define the Transformer model.

Examples

```
library(processpredictR)
library(eventdataR)
df <- prepare_examples(patients)
vocab_size(df)
```

Index

∗ **visualization**
plot.ppred_predictions, 5

character, *7*
confusion_matrix, 2
create_model, 3
create_vocabulary, 3

data.frame, *2, 3*, *8*

FALSE, *3*

get_vocabulary, 4

list, *3*, *8–10*
log, *6, 7*
logical, *3*

max_case_length, 4

NULL, *7*
num_outputs, 5
numeric, *8*

plot.ppred_predictions, 5
ppred_examples_df, *3–5*, 6, *6–10*
ppred_model, 6, *6, 7*
ppred_predictions, *2*, *5*, 6, *6*
prepare_examples, 6
print.ppred_model, 7
processpredictR, 8
processpredictR-package
(processpredictR), 8

split_train_test, 8
stack_layers, 9

table, *2*
tokenize, 9
TRUE, *3*

vocab_size, 10