

Package: restoptr (via r-universe)

June 24, 2026

Type Package

Title Ecological Restoration Planning

Version 1.1.1

Description Flexible framework for ecological restoration planning. It aims to identify priority areas for restoration efforts using optimization algorithms (based on Justeau-Allaire et al. 2021 <[doi:10.1111/1365-2664.13803](https://doi.org/10.1111/1365-2664.13803)>). Priority areas can be identified by maximizing landscape indices, such as the effective mesh size (Jaeger 2000 <[doi:10.1023/A:1008129329289](https://doi.org/10.1023/A:1008129329289)>), or the integral index of connectivity (Pascual-Hortal & Saura 2006 <[doi:10.1007/s10980-006-0013-z](https://doi.org/10.1007/s10980-006-0013-z)>). Additionally, constraints can be used to ensure that priority areas exhibit particular characteristics (e.g., ensure that particular places are not selected for restoration, ensure that priority areas form a single contiguous network). Furthermore, multiple near-optimal solutions can be generated to explore multiple options in restoration planning. The package leverages the 'Choco-solver' software to perform optimization using constraint programming (CP) techniques (<<https://choco-solver.org/>>).

License GPL (>= 3)

Encoding UTF-8

Language en-US

URL <https://dimitri-justeau.github.io/restoptr/>

BugReports <https://github.com/dimitri-justeau/restoptr/issues>

SystemRequirements Java (>= 11.0.12)

VignetteBuilder knitr

RoxygenNote 7.3.2

Imports utils, assertthat (>= 0.2.1), magrittr, crayon (>= 1.4.1), methods

Depends R (>= 4.1.0), terra (>= 1.6-17), rJava (>= 1.0.6), units (>= 0.8-0)

Suggests testthat (>= 2.0.1), knitr (>= 1.2.0), roxygen2 (>= 6.1.1),
rmarkdown (>= 1.10), landscapemetrics (>= 1.5.4), vegan (>= 2.5.7), cluster (>= 2.1.2), ggthemes, paletteer

Collate 'internal.R' 'add_available_areas_constraint.R'
'add_compactness_constraint.R' 'add_components_constraint.R'
'add_connected_constraint.R' 'add_locked_out_constraint.R'
'add_min_iic_constraint.R' 'add_min_mesh_constraint.R'
'add_nb_patches_constraint.R' 'add_no_new_patch_constraint.R'
'add_restorable_constraint.R' 'add_settings.R'
'is_java_available.R' 'package.R' 'preprocessing.R'
'restopt_component.R' 'restopt_problem.R' 'restopt_solution.R'
'set_max_iic_objective.R' 'set_max_mesh_objective.R'
'set_max_nb_pus_objective.R' 'set_max_restore_objective.R'
'set_min_nb_patches_objective.R' 'set_min_nb_pus_objective.R'
'set_min_restore_objective.R' 'set_no_objective.R' 'solve.R'
'terra_io.R' 'terra_utils.R' 'utils-pipe.R' 'zzz.R'

NeedsCompilation no

Author Dimitri Justeau-Allaire [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-4129-0764>>), Jeffrey O Hanson
[aut] (ORCID: <<https://orcid.org/0000-0002-4716-6134>>),
Ghislain Vieilledent [aut] (ORCID:
<<https://orcid.org/0000-0002-1685-4997>>), Guillaume Lannuzel
[aut], Philippe Vismara [aut], Xavier Lorca [aut], Philippe
Birnbaum [aut]

Maintainer Dimitri Justeau-Allaire <dimitri.justeau@gmail.com>

Config/pak/sysreqs

libgdal-dev gdal-bin libgeos-dev make default-jdk libproj-dev libsqlite3-dev libudunits2-dev

Repository <https://cranhaven.r-universe.dev>

Date/Publication 2026-06-17 01:02:00 UTC

RemoteUrl <https://github.com/cranhaven/cranhaven.r-universe.dev>

RemoteRef package/restopttr

RemoteSha 74463bb6475a18fac730f20e71d523e842bd0325

RemoteSubdir restopttr

Contents

add_available_areas_constraint	3
add_compactness_constraint	5
add_components_constraint	7
add_connected_constraint	8
add_locked_out_constraint	10
add_min_iic_constraint	12
add_min_mesh_constraint	14
add_nb_patches_constraint	15

add_no_new_patch_constraint	17
add_restorable_constraint	18
add_settings	20
area_to_nb_cells	22
cell_area	23
cell_width	24
get_aggregation_factor	25
get_aggregation_method	26
get_cell_area	27
get_constraints	27
get_existing_habitat	28
get_habitat_threshold	29
get_locked_out_areas	30
get_metadata	31
get_objective	31
get_original_habitat	32
get_restorable_habitat	33
get_settings	34
invert_vector	35
is_java_available	36
nb_cell_to_area	36
preprocess_input	37
print.RestoptProblem	38
restopt_problem	39
restopt_solution	41
restopttr	42
set_max_iic_objective	43
set_max_mesh_objective	45
set_max_nb_pus_objective	46
set_max_restore_objective	48
set_min_nb_patches_objective	49
set_min_nb_pus_objective	51
set_min_restore_objective	52
set_no_objective	54
solve.RestoptProblem	55

Index**58**

 add_available_areas_constraint

Add available areas constraint

Description

Add constraint to a restoration problem ([restopt_problem\(\)](#)) object to specify that only certain planning units can be selected for restoration activities.

Usage

```
add_available_areas_constraint(problem, data, touches = FALSE)
```

Arguments

problem	<code>restopt_problem()</code> Restoration problem object.
data	<code>terra::rast()</code> or <code>terra::vect()</code> Either a raster object containing binary values that indicate which planning units can be selected for restoration (i.e., only cells with a value equal one are available), or a vector object whose features correspond to the available areas.
touches	logical If the available area data is a vector, define whether the rasterization must include all pixels touching the polygons. (see <code>terra::rasterize()</code>). Useless if the data is raster data.

Details

Available areas constraints can be used to incorporate a wide range of criteria into restoration planning problems. They can be used to account for existing land-use practices, feasibility of restoration activities, and stakeholder preferences. For example, available areas constraints can be used to ensure that urban areas are not selected for restoration. Additionally, if restoration activities can only be implemented depending on certain conditions – such as places where landscape slope is not too steep – then available areas constraints could be used to ensure restoration activities are not prioritized for places where they could not be implemented. Furthermore, if stakeholders require solutions that do not prioritize particular places for restoration, then available areas constraints can also be used to achieve this. See `add_locked_out_constraint()`, which achieves the same as available areas constraint by defining areas that are NOT available for restoration. **Note:** The locked out constraint and the available are the same constraints, with a different input data. Thus, from a modelling perspective, `add_available_areas_constraint()` is just a pre processing layer in front of `add_locked_out_constraint()`. This is why if you print a `restopt` problem with an available areas constraint, you will see a locked out constraint.

Value

An updated restoration problem (`restopt_problem()`) object.

See Also

Other constraints: `add_compactness_constraint()`, `add_components_constraint()`, `add_connected_constraint()`, `add_locked_out_constraint()`, `add_min_iic_constraint()`, `add_min_mesh_constraint()`, `add_nb_patches_constraint()`, `add_no_new_patch_constraint()`, `add_restorable_constraint()`

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopt")
)
```

```
available <- vect(
  system.file("extdata", "accessible_areas.gpkg", package = "restoptr")
)

# plot data
plot(habitat_data)
plot(available, add=TRUE)

# create problem with available areas constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_max_iic_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_available_areas_constraint(available) %>%
add_settings(time_limit = 1)

# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)
```

add_compactness_constraint

Add constraint to limit compactness

Description

Add constraint to a restoration problem (`restopt_problem()`) object to specify the compactness of a solution.

Usage

```
add_compactness_constraint(problem, max_diameter, unit = "m")
```

Arguments

problem	restopt_problem() Restoration problem object.
max_diameter	numeric Maximum diameter value.
unit	unit object or a character that can be coerced to an area unit (see unit package), or "cells" for cell width of aggregated habitat raster. Corresponds to the unit of the maximum diameter. If the input habitat raster does not use a projected coordinate system, only "cells" is available.

Details

The compactness constraint is defined according to the diameter of the smallest enclosing circle which contains the center of selected planning units for restoration (see <https://w.wiki/4vfg>). The unit of the diameter corresponds either to a unit available in the [unit](#) package, or to planning unit width ("cells"). Note that, as the computation occurs on aggregated cells, if `max_diameter` is used with a different unit than "cells", it will be rounded to the closest corresponding number of cells. For example, a diameter of 4 cells means that no more than 4 cells can be found in line in the solution. In practice, this constraint is useful to ensure the feasibility of a restoration project, and to integrate economies of scale. Compact restoration areas are usually associated with lower costs and easier management, because it ensures that restoration sites are not too far away from each other (e.g. lower travel costs between sites, less areas to monitor, etc.).

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other constraints: [add_available_areas_constraint\(\)](#), [add_components_constraint\(\)](#), [add_connected_constraint\(\)](#), [add_locked_out_constraint\(\)](#), [add_min_iic_constraint\(\)](#), [add_min_mesh_constraint\(\)](#), [add_nb_patches_constraint\(\)](#), [add_no_new_patch_constraint\(\)](#), [add_restorable_constraint\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopttr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_restorable_constraint(
  min_restore = 200,
  max_restore = 300,
) %>%
add_compactness_constraint(1800, unit = "m")
```

```
# plot preprocessed data
plot(rast(list(p$data$existing_habitat, p$data$restorable_habitat)), nc = 2)

# print problem
print(p)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)
```

add_components_constraint

Add constraint to limit the number of connected components

Description

Add constraint to a restoration problem (`restopt_problem()`) object to specify the number of connected components that can be present within a solution.

Usage

```
add_components_constraint(problem, min_nb_components, max_nb_components)
```

Arguments

`problem` `restopt_problem()` Restoration problem object.
`min_nb_components` integer Minimum number of connected components.
`max_nb_components` integer Maximum number of connected components.

Details

A connected component is a spatially continuous set of planning units. This constraint applies on the set of planning units that are selected for restoration, and allows to specify a minimum and maximum number of connected components. In practice, this constraint is useful to ensure the feasibility of a restoration project, and to integrate economies of scale. Continuous restoration areas (i.e. less connected components) are usually associated with lower costs, because it ensures that restoration sites are not too far away from each other (e.g. lower travel costs between sites, less areas to monitor, etc.). On the other hand, it can be useful to enforce several disconnected restoration areas to ensure that hazards (e.g. fire) do not strike all planning units at the same time.

Value

An updated restoration problem (`restopt_problem()`) object.

See Also

Other constraints: `add_available_areas_constraint()`, `add_compactness_constraint()`, `add_connected_constraint()`, `add_locked_out_constraint()`, `add_min_iic_constraint()`, `add_min_mesh_constraint()`, `add_nb_patches_constraint()`, `add_no_new_patch_constraint()`, `add_restorable_constraint()`

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_restorable_constraint(
  min_restore = 10,
  max_restore = 100,
) %>%
add_components_constraint(1, 1)

# plot preprocessed data
plot(rast(list(p$data$existing_habitat, p$data$restorable_habitat)), nc = 2)

# print problem
print(p)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)
```

add_connected_constraint

Add constraint to ensure that the selected planning units for restoration are connected.

Description

Add constraint to a restoration problem ([restopt_problem\(\)](#)) object to specify the selected planning units are connected

Usage

```
add_connected_constraint(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

A connected area is such that there is a path between any to planning units within the area. This constraint applies on the set of planning units that are selected for restoration. In practice, this constraint is useful to ensure the feasibility of a restoration project, and to integrate economies of scale. Connected restoration areas are usually associated with lower costs, because it ensures that restoration sites are not too far away from each other (e.g. lower travel costs between sites, less areas to monitor, etc.). **Note** This constraint relies on the [add_components_constraint\(\)](#), with parameters set to enforce exactly one connected component. Also see [add_components_constraint](#) and [add_compactness_constraint](#).

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other constraints: [add_available_areas_constraint\(\)](#), [add_compactness_constraint\(\)](#), [add_components_constraint\(\)](#), [add_locked_out_constraint\(\)](#), [add_min_iic_constraint\(\)](#), [add_min_mesh_constraint\(\)](#), [add_nb_patches_constraint\(\)](#), [add_no_new_patch_constraint\(\)](#), [add_restorable_constraint\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_restorable_constraint(
  min_restore = 10,
  max_restore = 100,
) %>%
```

```

add_connected_constraint()

# plot preprocessed data
plot(rast(list(p$data$existing_habitat, p$data$restorable_habitat)), nc = 2)

# print problem
print(p)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)

```

```

add_locked_out_constraint
      Add locked out constraint

```

Description

Add constraint to a restoration problem (`restopt_problem()`) object to specify that certain planning units cannot be selected for restoration activities.

Usage

```
add_locked_out_constraint(problem, data, touches = FALSE)
```

Arguments

problem	<code>restopt_problem()</code> Restoration problem object.
data	<code>terra::rast()</code> or <code>terra::vect()</code> Either a raster object containing binary values that indicate which planning units cannot be selected for any restoration (i.e., cells with a value equal one are locked out from the solution), or a vector object whose features correspond to the locked out areas. See the function <code>add_available_areas_constraint()</code> to get a locked out constraint from allowed restoration areas.
touches	logical If the locked out data is a vector, define whether the rasterization must include all pixels touching the polygons. (see <code>terra::rasterize()</code>). Useless if the data is raster data.

Details

Locked out constraints can be used to incorporate a wide range of criteria into restoration planning problems. They can be used to account for existing land-use practices, feasibility of restoration activities, and stakeholder preferences. For example, locked out constraints can be used to ensure that urban areas are not selected for restoration. Additionally, if restoration activities can only be

implemented depending on certain conditions – such as places where landscape slope is not too steep – then locked out constraints could be used to ensure restoration activities are not prioritized for places where they could not be implemented. Furthermore, if stakeholders require solutions that do not prioritize particular places for restoration, then locked out constraints can also be used to achieve this. See `add_available_areas_constraint()`, which achieve the same as the locked out constraint by defining areas that ARE available for restoration.

Value

An updated restoration problem (`restopt_problem()`) object.

See Also

Other constraints: `add_available_areas_constraint()`, `add_compactness_constraint()`, `add_components_constraint()`, `add_connected_constraint()`, `add_min_iic_constraint()`, `add_min_mesh_constraint()`, `add_nb_patches_constraint()`, `add_no_new_patch_constraint()`, `add_restorable_constraint()`

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restoptr")
)

# plot data
plot(rast(list(habitat_data, locked_out_data)), nc = 2)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_max_iic_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_settings(time_limit = 1)

# print problem
print(p)

# solve problem
s <- solve(p)
```

```
# plot solution
plot(s)

## End(Not run)
```

```
add_min_iic_constraint
```

Add constraint to enforce a minimum integral index of connectivity (IIC) value

Description

Add constraint to a restoration problem (`restopt_problem()`) object to specify the minimum integral index of connectivity of a solution.

Usage

```
add_min_iic_constraint(
  problem,
  min_iic,
  distance_threshold = -1,
  unit = "m",
  precision = 4
)
```

Arguments

<code>problem</code>	<code>restopt_problem()</code> Restoration problem object.
<code>min_iic</code>	numeric Minimum IIC value (between 0 and 1).
<code>distance_threshold</code>	numeric greater than 0. Minimum distance (in <code>unit</code>) between two patches to consider them connected in the computation of the IIC. The default value -1 causes the function to use 1 aggregated cell as the distance threshold.
<code>unit</code>	unit object or a character that can be coerced to a distance unit (see <code>unit</code> package), or "cells" for cell width of aggregated habitat raster. Units of the <code>distance_threshold</code> parameter. If the input habitat raster does not use a projected coordinate system, only "cells" is available. Meters by default, expected if <code>distance_threshold</code> is set to its default value (-1), which causes the function to use 1 cell by default.
<code>precision</code>	integer Precision for calculations. Defaults to 4.

Details

The integral index of connectivity (IIC) is a graph-based inter-patch connectivity index based on a binary connection model (Pascual-Hortal & Saura, 2006). Its maximization in the context of restoration favours restoring the structural connectivity between large patches. IIC is unitless and

comprised between 0 (no connectivity) and 1 (all the landscape is habitat, thus fully connected). The `distance_threshold` parameter indicates to the solver how to construct the habitat graph, i.e. what is the minimum distance between two patches to consider them as connected. Note that, as the computation occurs on aggregated cells, if `distance_threshold` is used with a different unit than "cells", it will be rounded to the closest corresponding number of cells.

The effective mesh size (MESH) is a measure of landscape fragmentation based on the probability that two randomly chosen points are located in the same patch (Jaeger, 2000). Maximizing it in the context of restoration favours fewer and larger patches.

Value

An updated restoration problem (`restopt_problem()`) object.

References

Pascual-Hortal, L., & Saura, S. (2006). Comparison and development of new graph-based landscape connectivity indices: Towards the prioritization of habitat patches and corridors for conservation. *Landscape Ecology*, 21(7), 959-967. <https://doi.org/10.1007/s10980-006-0013-z>

See Also

[set_max_iic_objective](#)

Other constraints: [add_available_areas_constraint\(\)](#), [add_compactness_constraint\(\)](#), [add_components_constraint\(\)](#), [add_connected_constraint\(\)](#), [add_locked_out_constraint\(\)](#), [add_min_mesh_constraint\(\)](#), [add_nb_patches_constraint\(\)](#), [add_no_new_patch_constraint\(\)](#), [add_restorable_constraint\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopttr")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restopttr")
)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_min_iic_constraint(0.2) %>%
add_restorable_constraint(
  min_restore = 200,
  max_restore = 300,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_compactness_constraint(2500, unit = "m") %>%
```

```

add_settings(time_limit = 1)

# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)

```

```
add_min_mesh_constraint
```

Add constraint to enforce a minimum effective mesh size (MESH) value

Description

Add constraint to a restoration problem ([restopt_problem\(\)](#)) object to specify the minimum effective mesh size of a solution.

Usage

```
add_min_mesh_constraint(problem, min_mesh, precision = 4, unit = "ha")
```

Arguments

problem	restopt_problem() Restoration problem object.
min_mesh	numeric Minimum MESH value.
precision	integer Precision for calculations. Defaults to 4.
unit	unit object or a character that can be coerced to an area unit (see unit package), or "cells" for cell width of aggregated habitat raster. Corresponds to the unit of the minimum mesh value. If the input habitat raster does not use a projected coordinate system, only "cells" is available. Defaults to "ha".

Details

The effective mesh size (MESH) is a measure of landscape fragmentation based on the probability that two randomly chosen points are located in the same patch (Jaeger, 2000). Maximizing it in the context of restoration favours fewer and larger patches.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

References

Jaeger, J. A. G. (2000). Landscape division, splitting index, and effective mesh size: New measures of landscape fragmentation. *Landscape Ecology*, 15(2), 115-130. <https://doi.org/10.1023/A:1008129329289>

See Also

[set_max_mesh_objective](#)

Other constraints: [add_available_areas_constraint\(\)](#), [add_compactness_constraint\(\)](#), [add_components_constraint\(\)](#), [add_connected_constraint\(\)](#), [add_locked_out_constraint\(\)](#), [add_min_iic_constraint\(\)](#), [add_nb_patches_constraint\(\)](#), [add_no_new_patch_constraint\(\)](#), [add_restorable_constraint\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_restorable_constraint(
  min_restore = 200,
  max_restore = 300,
) %>%
add_min_mesh_constraint(min_mesh = 2500, unit = "ha")

# plot preprocessed data
plot(rast(list(p$data$existing_habitat, p$data$restorable_habitat)), nc = 2)

# print problem
print(p)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)
```

add_nb_patches_constraint

Add constraint to limit the number of patches (habitat + restoration)

Description

Add constraint to a restoration problem ([restopt_problem\(\)](#)) object to specify the number of patches (habitat + restoration) that can be present within a solution.

Usage

```
add_nb_patches_constraint(problem, min_nb_patches, max_nb_patches)
```

Arguments

`problem` [restopt_problem\(\)](#) Restoration problem object.
`min_nb_patches` integer Minimum number of patches.
`max_nb_patches` integer Maximum number of patches.

Details

A patch is a spatially continuous set of habitat and restoration planning units. This constraint applies on the union of the set of planning units that are selected for restoration and the initial habitat patches, and allows to specify a minimum and maximum number of patches. In practice, this constraint is useful to set simple targets for structural connectivity.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other constraints: [add_available_areas_constraint\(\)](#), [add_compactness_constraint\(\)](#), [add_components_constraint\(\)](#), [add_connected_constraint\(\)](#), [add_locked_out_constraint\(\)](#), [add_min_iic_constraint\(\)](#), [add_min_mesh_constraint\(\)](#), [add_no_new_patch_constraint\(\)](#), [add_restorable_constraint\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopt")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_restorable_constraint(
  min_restore = 10,
  max_restore = 100,
) %>%
add_nb_patches_constraint(1, 1)
```

```
# plot preprocessed data
plot(rast(list(p$data$existing_habitat, p$data$restorable_habitat)), nc = 2)

# print problem
print(p)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)
```

add_no_new_patch_constraint

Add constraint to forbid the creation of new patches.

Description

Add constraint to a restoration problem ([restopt_problem\(\)](#)) object to forbid the creation to new patches. All restored areas must be connected to an existing habitat area.

Usage

```
add_no_new_patch_constraint(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

A patch is a spatially continuous set of habitat and restoration planning units. This constraint applies on the union of the set of planning units that are selected for restoration and the initial habitat patches, and forbids the creation of new patches. All areas selected for restoration must be connected to initially existing habitat areas. This constraint is particularly useful for fragmentation reduction scenarios, where most of the time it is desirable to extend and merge existing patches, instead of creating new ones. In such cases, it also reduces the combinatorial complexity by filtering areas that cannot be connected to existing patches.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other constraints: [add_available_areas_constraint\(\)](#), [add_compactness_constraint\(\)](#), [add_components_constraint\(\)](#), [add_connected_constraint\(\)](#), [add_locked_out_constraint\(\)](#), [add_min_iic_constraint\(\)](#), [add_min_mesh_constraint\(\)](#), [add_nb_patches_constraint\(\)](#), [add_restorable_constraint\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopt")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_restorable_constraint(
  min_restore = 10,
  max_restore = 100,
) %>%
add_no_new_patch_constraint()

# plot preprocessed data
plot(rast(list(p$data$existing_habitat, p$data$restorable_habitat)), nc = 2)

# print problem
print(p)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)
```

add_restorable_constraint

Add constraint to specify the available amount of surface for restoration

Description

Add constraint to a restoration problem ([restopt_problem\(\)](#)) object to specify the available amount of surface for restoration

Usage

```

add_restorable_constraint(
  problem,
  min_restore,
  max_restore,
  min_proportion = 1,
  unit = "ha"
)

```

Arguments

problem	restopt_problem() Restoration problem object.
min_restore	numeric Minimum allowed area to restore in the solution.
max_restore	numeric Maximum allowed area to restore in the solution
min_proportion	float Minimum habitat proportion to consider a cell as restored.
unit	unit object or a character that can be coerced to an area unit (see unit package), or "cells" for number of cells from the original habitat raster. If the input habitat raster does not use a projected coordinate system, only "cells" is available.

Details

Given the `restorable_habitat` input raster in [restopt_problem](#), this constraint ensures that the total amount of restorable habitat in selected planning units is at least `min_restore` and at most `max_restore`. The unit of `min_restore` and `max_restore` can be either in a surface unit handled by the `unit` package, or in number of cells from the original habitat input raster ("cells"). The `min_proportion` parameter is a numeric between 0 and 1, and correspond to the minimum proportion of habitat area that needs to be restored in the planning unit to consider the planning unit as restored. This proportion is relative to the area of a planning unit, which is computed automatically from the input habitat raster. Note that planning unit area is considered uniform, and the distortion is not corrected. It could be using the `cellSize` function of the `terra` package, but this function is currently pretty slow for large rasters. If your problem is at regional scale, the distortion should be negligible. However, at larger scales, the best is to use an equal-area projected coordinate system.

Note that when a solution is found, the "maximum restorable habitat" is displayed, this value does not correspond to the `max_restore` parameter, but to the total area that can be restored in the selected planning units. The `max_restore` parameter is actually an upper bound of the minimum habitat that needs to be restored to reach the `min_proportion` of habitat in every selected planning units.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other constraints: [add_available_areas_constraint\(\)](#), [add_compactness_constraint\(\)](#), [add_components_constraint\(\)](#), [add_connected_constraint\(\)](#), [add_locked_out_constraint\(\)](#), [add_min_iic_constraint\(\)](#), [add_min_mesh_constraint\(\)](#), [add_nb_patches_constraint\(\)](#), [add_no_new_patch_constraint\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
add_restorable_constraint(
  min_restore = 200,
  max_restore = 300,
  min_proportion = 0.7
) %>%
add_compactness_constraint(5, unit = "cells")

# print problem
print(p)

# plot preprocessed data
plot(rast(list(get_existing_habitat(p),
              get_restorable_habitat(p),
              get_locked_out_areas(p))), nc = 3)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)
```

add_settings

Add settings

Description

Add settings to a restoration problem (`restopt_problem()`) object to customize the optimization procedure.

Usage

```
add_settings(
  problem,
  precision = 4,
```

```

    time_limit = 0,
    nb_solutions = 1,
    optimality_gap = 0,
    solution_name_prefix = "Solution "
  )

```

Arguments

problem	<code>restopt_problem()</code> Restoration problem object.
precision	integer Precision for calculations. Defaults to 4.
time_limit	integer Maximum permitted run time for optimization (seconds). Defaults to 0.
nb_solutions	integer Number of desired solutions. Defaults to 1.
optimality_gap	numeric Optimality gap (between 0 and 1). For example, an argument of 0.1 means that solutions should be within 10% of optimality. Defaults to 0, such that optimal solutions are returned.
solution_name_prefix	character Prefix for the name of solutions. Defaults to "Solution "

Value

An updated restoration problem (`restopt_problem()`) object.

Examples

```

## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
  add_settings(time_limit = 1, precision = 4, nb_solutions = 2)
# print problem
print(p)

## End(Not run)

```

area_to_nb_cells	<i>Compute the number of cells corresponding to a given area.</i>
------------------	---

Description

Compute the number of cells corresponding to a given area.

Usage

```
area_to_nb_cells(raster_layer, area, unit = "ha")
```

Arguments

raster_layer	<code>terra::rast()</code> Raster object.
area	numeric Area.
unit	unit object or a character that can be coerced to a unit (see unit package). Must be an area unit.

Details

The input raster must have a projected coordinate system. The distortion is not corrected. It could be using the `cellSize` function of the terra package, but this function is currently pretty slow for large rasters. If your problem is at regional scale, the distortion should be negligible. However, at larger scales, the best is to use an equal-area projected coordinate system.

Value

numeric The number of raster cell correspond to the given area.

Examples

```
## Not run:
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)
area_to_nb_cells(habitat_data, 20, unit = "ha")

## End(Not run)
```

cell_area	<i>Compute the area of a cell</i>
-----------	-----------------------------------

Description

Compute the area of a cell

Usage

```
cell_area(raster_layer, unit = "ha")
```

Arguments

`raster_layer` [terra::rast\(\)](#) Raster object.

`unit` unit object or a character that can be coerced to a unit (see `unit` package). Must be an area unit.

Details

The input raster must have a projected coordinate system. The distortion is not corrected. It could be using the `cellSize` function of the `terra` package, but this function is currently pretty slow for large rasters. If your problem is at regional scale, the distortion should be negligible. However, at larger scales, the best is to use an equal-area projected coordinate system.

Value

numeric The area of a cell in the desired unit.

Examples

```
## Not run:
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)
cell_area(habitat_data, "ha")

## End(Not run)
```

cell_width	<i>Compute the width of a cell</i>
------------	------------------------------------

Description

Compute the width of a cell

Usage

```
cell_width(raster_layer, unit = "m")
```

Arguments

raster_layer [terra::rast\(\)](#) Raster object.

unit unit object or a character that can be coerced to a unit (see unit package).
Must be an length unit.

Details

The input raster must have a projected coordinate system. The distortion is not corrected. It could be using the `cellSize` function of the terra package, but this function is currently pretty slow for large rasters. If your problem is at regional scale, the distortion should be negligible. However, at larger scales, the best is to use an equal-area projected coordinate system.

Value

numeric The width of a cell in the desired unit.

Examples

```
## Not run:  
habitat_data <- rast(  
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")  
)  
cell_width(habitat_data, "m")  
  
## End(Not run)
```

`get_aggregation_factor`*Retrieve the aggregation factor of a restopt problem.*

Description

Retrieve the aggregation factor of a restopt problem.

Usage

```
get_aggregation_factor(problem)
```

Arguments

`problem` [restopt_problem\(\)](#) Restoration problem object.

Value

numeric The aggregation factor of the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

get_aggregation_factor(problem)

## End(Not run)
```

`get_aggregation_method`*Retrieve the aggregation method of a restopt problem.*

Description

Retrieve the aggregation method of a restopt problem.

Usage

```
get_aggregation_method(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

character The aggregation method of the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7,
  lossless_aggregation = TRUE
)

get_aggregation_method(problem)

## End(Not run)
```

get_cell_area	<i>Retrieve the aggregated cell area of a restopt problem.</i>
---------------	--

Description

Retrieve the aggregated cell area of a restopt problem.

Usage

```
get_cell_area(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

[terra::rast\(\)](#) The aggregated cell area of the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

get_cell_area(problem)

## End(Not run)
```

get_constraints	<i>Retrieve the constraints of a restopt problem.</i>
-----------------	---

Description

Retrieve the constraints of a restopt problem.

Usage

```
get_constraints(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

list The constraints of the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

get_constraints(problem)

## End(Not run)
```

`get_existing_habitat` *Retrieve the existing (i.e. aggregated) habitat data.*

Description

Retrieve the existing (i.e. aggregated) habitat data.

Usage

```
get_existing_habitat(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

[terra::rast\(\)](#) The existing (aggregated) habitat data.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

plot(get_existing_habitat(problem))

## End(Not run)
```

get_habitat_threshold *Retrieve the habitat threshold parameter of a restopt problem.*

Description

Retrieve the habitat threshold parameter of a restopt problem.

Usage

```
get_habitat_threshold(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

numeric The habitat threshold parameter of the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
```

```
        aggregation_factor = 4,
        habitat_threshold = 0.7
    )

get_habitat_threshold(problem)

## End(Not run)
```

get_locked_out_areas *Retrieve the locked out areas of a restopt problem.*

Description

Retrieve the locked out areas of a restopt problem.

Usage

```
get_locked_out_areas(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

[terra::rast\(\)](#) The locked out areas of the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopt")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

get_locked_out_areas(problem)

## End(Not run)
```

get_metadata	<i>Restopt solution metadata</i>
--------------	----------------------------------

Description

Return the metadata associated with a restopt solution, which contains the characteristics of the solution. The unit for area characteristics can be chosen among "ha" (hectares), "m" (square meters), "km" (square kilometers), and "cells" (cells from the original input habitat raster). Note that the solving time is expressed in seconds.

Usage

```
get_metadata(restopt_solution, area_unit = "ha", distance_unit = "m")
```

Arguments

restopt_solution	restopt_solution() Restopt solution to this solution.
area_unit	unit object or a character that can be coerced to an area unit (see unit package), or "cells" for number of cells from the original habitat raster). Unit for areas. If the input habitat raster does not use a projected coordinate system, only "cells" is available. Default is "ha"
distance_unit	unit object or a character that can be coerced to an area unit (see unit package), or "cells" for number of cell width from the original habitat raster). Unit for distances. If the input habitat raster does not use a projected coordinate system, only "cells" is available. Default is "m"

Value

A list containing the characteristics of the restopt solution.

get_objective	<i>Retrieve the optimization objective of a restopt problem.</i>
---------------	--

Description

Retrieve the optimization objective of a restopt problem.

Usage

```
get_objective(problem)
```

Arguments

problem	restopt_problem() Restoration problem object.
---------	---

Value

RestoptObjective The optimization objective of the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

get_objective(problem)

## End(Not run)
```

get_original_habitat *Retrieve the original (i.e. not aggregated) habitat data.*

Description

Retrieve the original (i.e. not aggregated) habitat data.

Usage

```
get_original_habitat(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

[terra::rast\(\)](#) The original (i.e. not aggregated) habitat data.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)
```

```
# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

plot(get_original_habitat(problem))

## End(Not run)
```

get_restorable_habitat

Retrieve the restorable habitat (aggregated) data.

Description

Retrieve the restorable habitat (aggregated) data.

Usage

```
get_restorable_habitat(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

[terra::rast\(\)](#) The restorable habitat (aggregated) data.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

plot(get_restorable_habitat(problem))
```

```
## End(Not run)
```

get_settings	<i>Retrieve the settings of a restopt problem.</i>
--------------	--

Description

Retrieve the settings of a restopt problem.

Usage

```
get_settings(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Value

list The settings associated with the restopt problem.

Examples

```
## Not run:
#' # load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopt")
)

# create problem
problem <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

get_settings(problem)

## End(Not run)
```

invert_vector	<i>Invert a vector layer according to the extent of a restop problem.</i>
---------------	---

Description

Invert a vector layer according to the extent of a restop problem.

Usage

```
invert_vector(vector_layer, extent = NULL, filter = NULL)
```

Arguments

vector_layer	<code>terra::vect()</code> Vector layer.
extent	<code>terra::SpatExtent</code> Optional: you can specify another extent as the input vector layer extent for the inversion.
filter	Optional: filter to apply to x. Leave NULL for no filtering.

Details

Invert a vector layer according to its extent, or a user-specified extent. This function is useful to derive locked out areas from accessible areas, e.g. buffer around tracks.

Value

A `terra::vect()` Vector object.

Examples

```
## Not run:
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)
available <- vect(
  system.file("extdata", "accessible_areas.gpkg", package = "restoptr")
)
locked_out <- invert_vector(
  vector_layer = available,
  extent = ext(habitat_data),
  filter = available$ID==2
)

## End(Not run)
```

is_java_available	<i>Is Java is available?</i>
-------------------	------------------------------

Description

The **restoptr** package uses Java to perform optimization procedures. As such, it is important that Java is installed correctly when using this package. This function verifies if Java is available on the system.

Usage

```
is_java_available()
```

Value

A logical (TRUE or FALSE) value indicating if Java is available for usage.

nb_cell_to_area	<i>Compute the area corresponding to a given number of cells.</i>
-----------------	---

Description

Compute the area corresponding to a given number of cells.

Usage

```
nb_cell_to_area(raster_layer, nb_cells, unit = "ha")
```

Arguments

raster_layer	<code>terra::rast()</code> Raster object.
nb_cells	numeric Number of raster cells.
unit	unit object or a character that can be coerced to a unit (see unit package). Must be an area unit.

Details

The input raster must have a projected coordinate system. The distortion is not corrected. It could be using the `cellSize` function of the terra package, but this function is currently pretty slow for large rasters. If your problem is at regional scale, the distortion should be negligible. However, at larger scales, the best is to use an equal-area projected coordinate system.

Value

numeric The area corresponding to nb_cells in the desired unit.

Examples

```
## Not run:
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)
nb_cell_to_area(habitat_data, 20, unit = "ha")

## End(Not run)
```

```
preprocess_input      Restopr input preprocessing function.
```

Description

From a binary, possibly high resolution, habitat raster, this function produces three input rasters for restopt:

Usage

```
preprocess_input(habitat, habitat_threshold = 1, aggregation_factor = 1)
```

Arguments

habitat	<code>terra::rast()</code> Raster object containing binary values that indicate if each planning unit contains habitat or not. Cells with the value 1 must correspond to existing habitat. Cells with the value 0 must correspond to degraded (or simply non-habitat) areas. Finally, NA (or NO_DATA) cells are considered to be outside of the landscape.
habitat_threshold	numeric Number between 0 and 1 indicating, when the habitat raster is down-sampled, the minimum proportion of habitat cells (from the original raster) are required within the downsampled raster to be considered as habitat.
aggregation_factor	integer positive integer corresponding to the level of downsampling that will be applied to the habitat. This parameter is important to ensure the tractability of a problem.

Details

- The binary habitat raster (`existing_habitat`), which can be the same as the input (`aggregation_factor = 1`), but most often is a downsampled version of it, to ensure the tractability of the problem.
- The restorable habitat raster (`restorable_habitat`), which is a raster indicating how much habitat can be restored. If the `aggregation_factor = 1`, the restorable habitat raster is binary and the inverse of the habitat raster. Else, the surface of habitat is computed according to the spatial resolution, and the number of habitat pixel present in one larger aggregated cell.

- The cell area raster (`cell_area`), which correspond for each aggregated cell to the number of number of cells in the input raster. This is necessary because the cell area can be less than expected if the aggregated cell lies in the boundary of study area.

This preprocessing function produces the necessary inputs of a restopt problem from a single binary habitat raster (`habitat`), which can be at high resolution. Restopt solves a hard constrained combinatorial problem (it can be reduced to a constrained 0/1 knapsack problem, which is know to be NP-Complete), thus the input resolution might need to be reduced to ensure a tractable problem. Performing this downsampling in a systematic and reproducible way is the aim of this function, which relies on the `terra::aggregate()` function to do it. The `aggregation_factor` parameter indicates how much the resolution must be reduced. An aggregated pixel will contain at most `aggregation_factor^2` pixels from the input habitat raster (`cell_area` raster in this function outputs). If an aggregated pixel is close to the spatial boundaries of the problem (i.e. NA cells), it can contain less than `aggregation_factor^2` fine grained pixels. The `habitat_threshold` parameter indicates the minimum proportion of habitat pixels (relative to `cell_area`) whose value is 1 to consider an aggregated pixel as habitat (`downsampled_habitat` output raster). The `restorable_area` output raster correspond to the number of pixel with value 0 in aggregated pixels.

Value

A list: `list(existing_habitat=downsampled_habitat, restorable_habitat=restorable_habitat, cell_area=cell_area)`

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopttr"))
data <- preprocess_input(
  habitat = habitat_data,
  habitat_threshold = 0.7,
  aggregation_factor = 16
)

## End(Not run)
```

`print.RestoptProblem` *Print a restoration optimization problem*

Description

Display information about a restoration optimization problem.

Usage

```
## S3 method for class 'RestoptProblem'
print(x, ...)
```

Arguments

x `restopt_problem()` Restoration problem object.
... Arguments not used.

Examples

```
## Not run:  
#' # load data  
habitat_data <- rast(  
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")  
)  
  
# create problem  
p <- restopt_problem(  
  existing_habitat = habitat_data,  
  aggregation_factor = 4,  
  habitat_threshold = 0.7  
)  
  
# print problem  
print(p)  
  
## End(Not run)
```

restopt_problem *Restoration optimization problem*

Description

Create a new restoration optimization problem (`RestoptProblem`) using data that describe the spatial distribution of existing habitat (potentially at high resolution), and parameters to derive a down-sampled existing habitat raster, suitable for a tractable optimization, and a restorable habitat raster. Constraints can be added to a `restopt` problem using `add_***_constraint()` functions, and an optimization objective can be set using `set_***_objective()` functions.

Usage

```
restopt_problem(  
  existing_habitat,  
  habitat_threshold = 1,  
  aggregation_factor = 1,  
  lossless_aggregation = FALSE  
)
```

Arguments`existing_habitat`

`terra::rast()` Raster object containing binary values that indicate if each planning unit contains habitat or not. Cells with the value 1 must correspond to existing habitat. Cells with the value 0 must correspond to degraded (or simply non-habitat) areas. Finally, NA (or NO_DATA) cells are considered to be outside of the landscape. This raster can have a high resolution, the `aggregation_factor` and the `habitat_threshold` parameters, described below, will be used to down sample the habitat raster to a tractable resolution for the optimization engine, and automatically derive the restorable habitat raster.

`habitat_threshold`

numeric number between 0 and 1, which corresponds to the minimum proportion of habitat that must be present within an aggregated pixel to consider it as an habitat pixel.

`aggregation_factor`

integer Integer greater than 1, which corresponds to the aggregation factor for down sampling the data. For example, if `aggregation_factor = 2`, aggregated pixel will contain 4 original pixel. See `terra::aggregate()` for more details.

`lossless_aggregation`

logical If TRUE, uses restopt Java aggregation method, which is lossless, as it creates a two levels hierarchical square grid, in which planning units are packs of aggregated pixel that follow the geometry of the habitat raster. In this case, the `habitat_threshold` parameter is not needed anymore. If FALSE, uses restopt original aggregation method, which is lossy because it creates a single aggregated grid, where a planning unit can contain both habitat and non-habitat pixels.

Details

This function creates the base restoration optimization problem object, that can be further extended with constraints and optimization objectives. One input rasters is necessary to instantiate a restopt problem: the `existing_habitat` raster (potentially with high resolution). This raster must contains data about where are habitat areas (raster value 1), non-habitat areas (raster value 0), and areas that must not be considered during the solving procedure (NA or NO_DATA). The `aggregation_factor` parameter is used to down sample the `existing_habitat` to a resolution that will be tractable for the optimization engine, and the `habitat_threshold` parameter indicates the minimum proportion of habitat required in aggregated habitat pixels to consider them as habitat. Note that An aggregated pixel will contain at most $aggregation_factor^2$ pixels from the input habitat raster (`cell_area` raster in this function outputs). If an aggregated pixel is close to the spatial boundaries of the problem (i.e. NA cells), it can contain less than $aggregation_factor^2$ fine grained pixel. You can get the results of this preprocessing phase using the following methods: `get_original_habitat()` (original habitat), `get_existing_habitat()` (aggregated habitat), `get_cell_area()` (number of pixels in each aggregated cells), and `get_restorable_area()` (amount of restorable area – in number of original raster pixels).

Value

A new restoration problem (`RestoptProblem`) object.

None.

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 4,
  habitat_threshold = 0.7
)

# Plot down sampled data
plot(c(p$data$existing_habitat, p$data$restorable_habitat))

# print problem
print(p)

## End(Not run)
```

restopt_solution	<i>Restopt solution</i>
------------------	-------------------------

Description

An object representing a restopt problem solution. It is basically a SpatRaster with a few metadata attributes added.

Usage

```
restopt_solution(restopt_problem, solution_raster, metadata, id_solution = 1)
```

Arguments

restopt_problem	<code>restopt_problem()</code> Reference to the problem corresponding to this solution.
solution_raster	<code>terra::rast()</code> Solution raster.
metadata	<code>list</code> List containing metadata attributes of the solution.
id_solution	<code>integer</code> Identifier of the solution.

Value

A new restoration problem solution (`restopt_solution()`).

restoptr

restoptr: *Ecological Restoration Planning*

Description

The `restoptr` package relies on Constraint Programming (CP) to build and solve ecological restoration planning problems. A `restoptr` problem starts from an existing habitat (raster), where the aim is to identify optimal areas that are suitable for restoration. Several constraints are available to define what is expected for a suitable area for (e.g. it must be connected, compact, must respect a budget, etc). Several optimization objective are also available to define what is a good restoration area (e.g. it must reduce fragmentation, increase ecological connectivity, minimize costs, etc.). `restoptr` relies on advanced landscape indices such as the effective mesh size (Jaeger, 2000), or the integral index of connectivity (Pascual-Hortal & Saura, 2006) to address complex restoration planning problems.

Details

`restoptr` relies on Choco-solver (<https://choco-solver.org/>), an open-source Java CP solver (Prud'homme et al., 2017). The computationally intensive solving part is thus delegated to Java (see `restopt`, <https://github.com/dimitri-justeau/restopt>), and the communication between R and Java is handled with the `rJava` package. Therefore, a Java Runtime Environment (≥ 8) is necessary to use `restopt`.

Note that the methodology used in `restoptr` was first described in Justeau-Allaire et al. (2021), but `restoptr` provides much more flexibility, new features (e.g. reliable and consistent data preprocessing), new constraints, new optimization objectives, and an improved computational efficiency. Also note that the API was inspired by the `prioritizr` package.

This package contains several vignettes to detail its usage and showcase its features. You can explore these vignettes using `browseVignettes("restoptr")`

Author(s)

Maintainer: Dimitri Justeau-Allaire <dimitri.justeau@gmail.com> ([ORCID](#))

Authors:

- Jeffrey O Hanson <jeffrey.hanson@uqconnect.edu.au> ([ORCID](#))
- Ghislain Vieilledent ([ORCID](#))
- Guillaume Lannuzel
- Philippe Vismara
- Xavier Lorca
- Philippe Birnbaum

References

Hanson JO, Schuster R, Morrell N, Strimas-Mackey M, Edwards BPM, Watts ME, Arcese P, Bennett J, Possingham HP (2022). prioritizr: Systematic Conservation Prioritization in R. R package version 7.1.1. Available at <https://CRAN.R-project.org/package=prioritizr>.

Jaeger, J. A. G. (2000). Landscape division, splitting index, and effective mesh size: New measures of landscape fragmentation. *Landscape Ecology*, 15(2), 115-130.

Justeau-Allaire, D., Vieilledent, G., Rinck, N., Vismara, P., Lorca, X., & Birnbaum, P. (2021). Constrained optimization of landscape indices in conservation planning to support ecological restoration in New Caledonia. *Journal of Applied Ecology*, 58(4), 744-754.

Pascual-Hortal, L., & Saura, S. (2006). Comparison and development of new graph-based landscape connectivity indices: Towards the prioritization of habitat patches and corridors for conservation. *Landscape Ecology*, 21(7), 959-967.

Prud'homme, C., Fages, J.-G., & Lorca, X. (2017). Choco documentation.

See Also

Useful links:

- <https://dimitri-justeau.github.io/restoptr/>
- Report bugs at <https://github.com/dimitri-justeau/restoptr/issues>

set_max_iic_objective *Set an objective to maximize the integral index of connectivity*

Description

Specify that a restoration problem (`restopt_problem()`) should the integral index of connectivity (IIC).

Usage

```
set_max_iic_objective(problem, distance_threshold = -1, unit = "m")
```

Arguments

problem	<code>restopt_problem()</code> Restoration problem object.
distance_threshold	numeric greater than 0. Minimum distance (in unit) between two patches to consider them connected in the computation of the IIC. The default value -1 causes the function to use 1 aggregated cell as the distance threshold.
unit	unit object or a character that can be coerced to a distance unit (see <code>unit</code> package), or "cells" for cell width of aggregated habitat raster. Units of the <code>distance_threshold</code> parameter. If the input habitat raster does not use a projected coordinate system, only "cells" is available. Meters by default, expected if <code>distance_threshold</code> is set to its default value (-1), which causes the function to use 1 cell by default.

Details

The integral index of connectivity (IIC) is a graph-based inter-patch connectivity index based on a binary connection model (Pascual-Hortal & Saura, 2006). Its maximization in the context of restoration favours restoring the structural connectivity between large patches. IIC is unitless and comprised between 0 (no connectivity) and 1 (all the landscape is habitat, thus fully connected). The `distance_threshold` parameter indicates to the solver how to construct the habitat graph, i.e. what is the minimum distance between two patches to consider them as connected. Note that, as the computation occurs on aggregated cells, if `distance_threshold` is used with a different unit than "cells", it will be rounded to the closest corresponding number of cells.

Value

An updated restoration problem (`restopt_problem()` object).

References

Pascual-Hortal, L., & Saura, S. (2006). Comparison and development of new graph-based landscape connectivity indices: Towards the prioritization of habitat patches and corridors for conservation. *Landscape Ecology*, 21(7), 959-967. <https://doi.org/10.1007/s10980-006-0013-z>

See Also

Other objectives: `set_max_mesh_objective()`, `set_max_nb_pus_objective()`, `set_max_restore_objective()`, `set_min_nb_patches_objective()`, `set_min_nb_pus_objective()`, `set_min_restore_objective()`, `set_no_objective()`

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopttr")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restopttr")
)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_max_iic_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_settings(time_limit = 1)
```

```
# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)
```

set_max_mesh_objective

Set an objective to maximize effective mesh size

Description

Specify that a restoration problem ([restopt_problem\(\)](#)) should maximize effective mesh size.

Usage

```
set_max_mesh_objective(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

The effective mesh size (MESH) is a measure of landscape fragmentation based on the probability that two randomly chosen points are located in the same patch (Jaeger, 2000). Maximizing it in the context of restoration favours fewer and larger patches.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

References

Jaeger, J. A. G. (2000). Landscape division, splitting index, and effective mesh size: New measures of landscape fragmentation. *Landscape Ecology*, 15(2), 115-130. <https://doi.org/10.1023/A:1008129329289>

See Also

Other objectives: [set_max_iic_objective\(\)](#), [set_max_nb_pus_objective\(\)](#), [set_max_restore_objective\(\)](#), [set_min_nb_patches_objective\(\)](#), [set_min_nb_pus_objective\(\)](#), [set_min_restore_objective\(\)](#), [set_no_objective\(\)](#)

Examples

```

## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopt")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restopt")
)

# plot data
plot(rast(list(habitat_data, locked_out_data)), nc = 2)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_max_mesh_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_settings(time_limit = 1)

# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)

```

```
set_max_nb_pus_objective
```

Set an objective to maximize the number of planning units

Description

Specify that a restoration problem ([restopt_problem\(\)](#)) should maximize the number of planning units.

Usage

```
set_max_nb_pus_objective(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

Planning units correspond to aggregated cells from the original dataset. Maximizing the number of planning units increased the spatial extent of the restoration area. This can be useful when the budget is limited and the aim is to restore the largest possible extent.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other objectives: [set_max_iic_objective\(\)](#), [set_max_mesh_objective\(\)](#), [set_max_restore_objective\(\)](#), [set_min_nb_patches_objective\(\)](#), [set_min_nb_pus_objective\(\)](#), [set_min_restore_objective\(\)](#), [set_no_objective\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restoptr")
)

# plot data
plot(rast(list(habitat_data, locked_out_data)), nc = 2)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_max_nb_pus_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_settings(time_limit = 1)
```

```
# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)
```

set_max_restore_objective

Set an objective to maximize the amount restoration area.

Description

Specify that a restoration problem ([restopt_problem\(\)](#)) should maximize the restoration area needed to reach the habitat proportion threshold specified in the problem description.

Usage

```
set_max_restore_objective(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

The restoration area corresponds to the minimum amount of area that must be restored in the selected planning units to reach the minimum habitat proportion threshold specified in the problem description,

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other objectives: [set_max_iic_objective\(\)](#), [set_max_mesh_objective\(\)](#), [set_max_nb_pus_objective\(\)](#), [set_min_nb_patches_objective\(\)](#), [set_min_nb_pus_objective\(\)](#), [set_min_restore_objective\(\)](#), [set_no_objective\(\)](#)

Examples

```

## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restoptr")
)

# plot data
plot(rast(list(habitat_data, locked_out_data)), nc = 2)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
  set_max_restore_objective() %>%
  add_restorable_constraint(
    min_restore = 5,
    max_restore = 5,
  ) %>%
  add_locked_out_constraint(data = locked_out_data) %>%
  add_settings(time_limit = 1)

# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)

```

```
set_min_nb_patches_objective
```

Set an objective to minimize the number of patches (habitat + restored areas)

Description

Specify that a restoration problem (`restopt_problem()`) should minimize the number of patches (habitat + restored areas).

Usage

```
set_min_nb_patches_objective(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

Patches correspond to the union of existing habitat and restored areas. Minimizing the number of patches improves structural connectivity in the habitat class.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other objectives: [set_max_iic_objective\(\)](#), [set_max_mesh_objective\(\)](#), [set_max_nb_pus_objective\(\)](#), [set_max_restore_objective\(\)](#), [set_min_nb_pus_objective\(\)](#), [set_min_restore_objective\(\)](#), [set_no_objective\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restoptr")
)

# plot data
plot(rast(list(habitat_data, locked_out_data)), nc = 2)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_min_nb_patches_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_settings(time_limit = 1)
```

```
# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)
```

set_min_nb_pus_objective

Set an objective to minimize the number of planning units

Description

Specify that a restoration problem ([restopt_problem\(\)](#)) should minimize the number of planning units.

Usage

```
set_min_nb_pus_objective(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

Planning units correspond to aggregated cells from the original dataset. Minimizing the number of planning units reduces the spatial extent of the restoration area.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other objectives: [set_max_iic_objective\(\)](#), [set_max_mesh_objective\(\)](#), [set_max_nb_pus_objective\(\)](#), [set_max_restore_objective\(\)](#), [set_min_nb_patches_objective\(\)](#), [set_min_restore_objective\(\)](#), [set_no_objective\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restopt")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restopt")
)

# plot data
plot(rast(list(habitat_data, locked_out_data)), nc = 2)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_min_nb_pus_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_settings(time_limit = 1)

# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)
```

set_min_restore_objective

Set an objective to minimize the amount restoration area.

Description

Specify that a restoration problem ([restopt_problem\(\)](#)) should minimize the restoration area needed to reach the habitat proportion threshold specified in the problem description.

Usage

```
set_min_restore_objective(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

The restoration area corresponds to the minimum amount of area that must be restored in the selected planning units to reach the minimum habitat proportion threshold specified in the problem description,

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other objectives: [set_max_iic_objective\(\)](#), [set_max_mesh_objective\(\)](#), [set_max_nb_pus_objective\(\)](#), [set_max_restore_objective\(\)](#), [set_min_nb_patches_objective\(\)](#), [set_min_nb_pus_objective\(\)](#), [set_no_objective\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

locked_out_data <- rast(
  system.file("extdata", "locked_out.tif", package = "restoptr")
)

# plot data
plot(rast(list(habitat_data, locked_out_data)), nc = 2)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_min_restore_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_locked_out_constraint(data = locked_out_data) %>%
add_settings(time_limit = 1)
```

```
# print problem
print(p)

# solve problem
s <- solve(p)

# plot solution
plot(s)

## End(Not run)
```

set_no_objective	<i>Configure the solver to only satisfy the constraints, without optimization objective</i>
------------------	---

Description

Specify that a restoration problem ([restopt_problem\(\)](#)) should satisfy the constraints without optimization objective.

Usage

```
set_no_objective(problem)
```

Arguments

problem [restopt_problem\(\)](#) Restoration problem object.

Details

Using `set_no_objective()` in a `restopt` problem, the solver will return the first solution found satisfying the constraint, without any optimization objective. This "no objective" setting is set by default when creating a `restopt` problem.

Value

An updated restoration problem ([restopt_problem\(\)](#)) object.

See Also

Other objectives: [set_max_iic_objective\(\)](#), [set_max_mesh_objective\(\)](#), [set_max_nb_pus_objective\(\)](#), [set_max_restore_objective\(\)](#), [set_min_nb_patches_objective\(\)](#), [set_min_nb_pus_objective\(\)](#), [set_min_restore_objective\(\)](#)

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

# create problem
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>% set_no_objective()

# print problem
print(p)

# Solve problem
s <- solve(p)
# plot solution
plot(s)

## End(Not run)
```

solve.RestoptProblem *Solve a restoration optimization problem*

Description

Solve a restoration optimization problem to generate a solution.

Usage

```
## S3 method for class 'RestoptProblem'
solve(a, b, ...)
```

Arguments

a	<code>restopt_problem()</code> Restoration problem object.
b	Argument not used.
...	Additional arguments: <code>verbose</code> (logical) if TRUE, output solver logs. (FALSE by default) <code>search_strategy</code> (character) specify the solver's search strategy, among: "" -> default "RANDOM", "DOM_OVER_W_DEG", "DOM_OVER_W_DEG_REF", "MIN_DOM_LB", "MIN_DOM_UB", "ACTIVITY_BASED", "CONFLICT_HISTORY", "FAILURE_RATE", "FAILURE_LENGTH" <code>lns</code> (logical) if TRUE, activate Large Neighborhood Search (LNS). LNS can boost the optimization efficiency for

large problems, with the price of less guarantees. Warning: it is highly recommended to set a time limit when using LNS because optimality proof may become unreachable (it depends on the characteristics of the problem), causing the solver to run forever without a time limit. Also, while LNS may boost the solver, it is very dependent on the problem's setting and size. It is recommended to first try solving a problem without LNS, and then try it if the results are not satisfactory.

Details

This function relies on the Choco-solver (<https://choco-solver.org/>) to solve a restoration optimization problem. If the solver finds a solution, it outputs a raster with 5 possible values: NA : NA (or NO_DATA) areas from the input habitat raster. 0 : non-habitat areas that were locked out. 1 : non-habitat areas that were available for selection. 2 : habitat areas. 3 : selected planning units for restoration. If the solve function return a no-solution error, it is either because the solver could not find a solution within the time limit that was set (see [add_settings](#)), or because the solver has detected that this is not possible to satisfy the constraints (the constraints are contradictory). In the first case, you can try to increase the time limit. In the second case, you should modify your targets.

Value

A `restopt_solution()` object.

Examples

```
## Not run:
# load data
habitat_data <- rast(
  system.file("extdata", "habitat_hi_res.tif", package = "restoptr")
)

available <- vect(
  system.file("extdata", "accessible_areas.gpkg", package = "restoptr")
)

# create problem with locked out constraints
p <- restopt_problem(
  existing_habitat = habitat_data,
  aggregation_factor = 16,
  habitat_threshold = 0.7
) %>%
set_max_mesh_objective() %>%
add_restorable_constraint(
  min_restore = 5,
  max_restore = 5,
) %>%
add_available_areas_constraint(available) %>%
add_settings(time_limit = 1)

# print problem
print(p)
```

```
# solve problem  
s <- solve(p)  
  
# plot solution  
plot(s)  
  
## End(Not run)
```

Index

* constraints

- add_available_areas_constraint, 3
- add_compactness_constraint, 5
- add_components_constraint, 7
- add_connected_constraint, 8
- add_locked_out_constraint, 10
- add_min_iic_constraint, 12
- add_min_mesh_constraint, 14
- add_nb_patches_constraint, 15
- add_no_new_patch_constraint, 17
- add_restorable_constraint, 18

* objectives

- set_max_iic_objective, 43
- set_max_mesh_objective, 45
- set_max_nb_pus_objective, 46
- set_max_restore_objective, 48
- set_min_nb_patches_objective, 49
- set_min_nb_pus_objective, 51
- set_min_restore_objective, 52
- set_no_objective, 54

- add_available_areas_constraint, 3, 6, 8, 9, 11, 13, 15, 16, 18, 19
- add_compactness_constraint, 4, 5, 8, 9, 11, 13, 15, 16, 18, 19
- add_components_constraint, 4, 6, 7, 9, 11, 13, 15, 16, 18, 19
- add_connected_constraint, 4, 6, 8, 8, 11, 13, 15, 16, 18, 19
- add_locked_out_constraint, 4, 6, 8, 9, 10, 13, 15, 16, 18, 19
- add_min_iic_constraint, 4, 6, 8, 9, 11, 12, 15, 16, 18, 19
- add_min_mesh_constraint, 4, 6, 8, 9, 11, 13, 14, 16, 18, 19
- add_nb_patches_constraint, 4, 6, 8, 9, 11, 13, 15, 15, 18, 19
- add_no_new_patch_constraint, 4, 6, 8, 9, 11, 13, 15, 16, 17, 19

- add_restorable_constraint, 4, 6, 8, 9, 11, 13, 15, 16, 18, 18

- add_settings, 20, 56
- area_to_nb_cells, 22

- cell_area, 23
- cell_width, 24

- get_aggregation_factor, 25
- get_aggregation_method, 26
- get_cell_area, 27
- get_constraints, 27
- get_existing_habitat, 28
- get_habitat_threshold, 29
- get_locked_out_areas, 30
- get_metadata, 31
- get_objective, 31
- get_original_habitat, 32
- get_restorable_habitat, 33
- get_settings, 34

- integer, 41
- invert_vector, 35
- is_java_available, 36

- list, 41

- nb_cell_to_area, 36

- preprocess_input, 37
- print.RestoptProblem, 38

- restopt_problem, 19, 39
- restopt_problem(), 3–14, 16–21, 25–34, 39, 41, 43–55
- restopt_solution, 41
- restopt_solution(), 31, 56
- restoptr, 42
- restoptr-package (restoptr), 42
- set_max_iic_objective, 13, 43, 45, 47, 48, 50, 51, 53, 54

set_max_mesh_objective, [15](#), [44](#), [45](#), [47](#), [48](#),
[50](#), [51](#), [53](#), [54](#)
set_max_nb_pus_objective, [44](#), [45](#), [46](#), [48](#),
[50](#), [51](#), [53](#), [54](#)
set_max_restore_objective, [44](#), [45](#), [47](#), [48](#),
[50](#), [51](#), [53](#), [54](#)
set_min_nb_patches_objective, [44](#), [45](#), [47](#),
[48](#), [49](#), [51](#), [53](#), [54](#)
set_min_nb_pus_objective, [44](#), [45](#), [47](#), [48](#),
[50](#), [51](#), [53](#), [54](#)
set_min_restore_objective, [44](#), [45](#), [47](#), [48](#),
[50](#), [51](#), [52](#), [54](#)
set_no_objective, [44](#), [45](#), [47](#), [48](#), [50](#), [51](#), [53](#),
[54](#)
solve.RestoptProblem, [55](#)

terra::rast(), [4](#), [10](#), [22–24](#), [27](#), [28](#), [30](#), [32](#),
[33](#), [36](#), [37](#), [40](#), [41](#)
terra::SpatExtent, [35](#)
terra::vect(), [4](#), [10](#), [35](#)