

Package: simgof (via r-universe)

October 13, 2026

Title Simultaneous Goodness-of-Fits Tests

Version 1.0.2

Description Routine that allows the user to run several goodness-of-fit tests. It also combines the tests and returns a properly adjusted family-wise p value. Details can be found in [doi:10.48550/arXiv.2007.04727](https://doi.org/10.48550/arXiv.2007.04727).

Depends R (>= 3.1.0)

Imports ddst, stats, graphics

License GPL-2

Encoding UTF-8

NeedsCompilation no

LazyData true

RoxygenNote 7.1.1

Author Wolfgang Rolke [aut, cre]
(<https://orcid.org/0000-0002-3514-726X>)

Maintainer Wolfgang Rolke <wolfgang.rolke@upr.edu>

Repository <https://cranhaven.r-universe.dev>

Date/Publication 2026-09-13 03:02:00 UTC

RemoteUrl <https://github.com/cranhaven/cranhaven.r-universe.dev>

RemoteRef package/simgof

RemoteSha a17bf4035ec6cfbfa3676e850f3fcacfb93730b0

RemoteSubdir simgof

Contents

chisquare.test	2
simgof.test	2
spreadout	3
TS	4

Index	6
--------------	----------

chisquare.test	<i>chisquare.test</i>
----------------	-----------------------

Description

This function does the chisquare test

Usage

```
chisquare.test(x, case, which = "RGd")
```

Arguments

x	data set
case	setup info
which	type of binning (either RGd, Equal Size or Equal Prob)

Value

A numeric vector of length 1 with the value of the chi-square statistic.

Examples

```
case <- list(B=1000, param = NULL, n = 1000, pnull = function(x, param) punif(x),
            rnull = function(n, param) runif(n), qnull = function(x, param) qunif(x),
            est.mle = function(x) NA, nbins = 10)
x <- runif(1000)
chisquare.test(x, case)
```

simgof.test	<i>simgof.test</i>
-------------	--------------------

Description

This function performs a number of gof tests and rejects the null if any of the tests does so. Then it finds the adjusted p-value.

Usage

```
simgof.test(
  x,
  pnull,
  rnull,
  qnull = function(x) NULL,
  do.estimation = TRUE,
  estimate = function(x) NULL,
```

```

include.methods = c(rep(TRUE, 7), rep(FALSE, 9)),
B = 10000,
lambda,
nbins = NULL
)

```

Arguments

x	data set
pnull	distribution function under the null hypothesis
rnull	routine to generate data under the null hypothesis
qnull	quantile function under the null hypothesis
do.estimation	TRUE if parameters are to be estimated
estimate	routine for parameter estimation
include.methods	which methods should be used, a vector of length 16 of T/F
B	=10000 number of simulation runs
lambda	rate of Poisson if sample size is random
nbins	number of bins for chisquare test

Value

A numeric vector of p values

Examples

```

x <- runif(1000)
pnull <- function(x) x
rnull <- function(n) runif(n)
qnull <- function(x) x
simgof.test(x, pnull, rnull, qnull, FALSE, B=500)
x <- rnorm(1000, 100, 20)
pnull <- function(x, param) pnorm(x, param[1], param[2])
rnull <- function(n, param) rnorm(x, param[1], param[2])
qnull <- function(x, param) qnorm(x, param[1], param[2])
estimate <- function(x) c(mean(x), sd(x))
simgof.test(x, pnull, rnull, qnull, TRUE, estimate, B=500)

```

spreadout

spreadout

Description

This function unbins data. If qnull is given it uses quantiles, otherwise uniform

Usage

spreadout(x, case)

Arguments

x data set
case setup info

Value

A numeric vector of observations without ties.

Examples

```
case <- list(B=1000, param = NULL, n = 1000, pnull = function(x, param) punif(x),
  rnull = function(n, param) runif(n), qnull = function(x, param) qunif(x),
  est.mle = function(x) NA, nbins = 10)
y=runif(1000)
bins=seq(0, 1, length=11)
counts=hist(y, bins, plot=FALSE)$counts
x=list(bins=bins,counts=counts)
spreadout(x, case)
```

TS	TS
----	----

Description

This function finds various gof statistics

Usage

TS(x, case)

Arguments

x data
case setup info

Value

A numeric vector with the values of various test statistics.

Examples

```
case <- list(B=1000, param = NULL, n = 1000, pnull = function(x, param)
  punif(x), rnull = function(n, param) runif(n), qnull = function(x, param)
  qunif(x), est.mle = function(x) NA, nbins = 10)
case$methods=c("KS", "AD", "CdM", "W", "ZA", "ZK", "ZC")
x <- runif(1000)
TS(x, case)
```

Index

chisquare.test, [2](#)

singof.test, [2](#)

spreadout, [3](#)

TS, [4](#)