

Package: tremendousr (via r-universe)

June 1, 2026

Title Easily Send Rewards and Incentives with 'Tremendous' from R

Version 1.0.0

Description A slightly-opinionated R interface for the 'Tremendous' API (<<https://www.tremendous.com/>>). In addition to supporting GET and POST requests, 'tremendousr' has, dare I say, tremendously intuitive functions for sending digital rewards and incentives directly from R.

License MIT + file LICENSE

Encoding UTF-8

Language es

RoxygenNote 7.1.1.9000

Imports cli, crayon, crul, jsonlite

Suggests testthat (>= 3.0.0), clipr, vcr (>= 0.6.0), knitr, rmarkdown

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Jonathan Trattner [aut, cre]
(<<https://orcid.org/0000-0002-1097-7603>>), Scott Chamberlain [ctb] (Utility functions `err_catcher()` and `trem_ua()` from chimpr package.), R Computing Lab at Wake Forest University [fnd]

Maintainer Jonathan Trattner <jdt@jdtrat.com>

Config/pak/sysreqs libssl-dev

Repository <https://cranhaven.r-universe.dev>

Date/Publication 2026-06-01 04:02:00 UTC

RemoteUrl <https://github.com/cranhaven/cranhaven.r-universe.dev>

RemoteRef package/tremendousr

RemoteSha ed7be8561aa50b9a4fc769103bdfd471c0b7c6cc

RemoteSubdir tremendousr

Contents

trem_client_new	2
trem_delete	3
trem_get	4
trem_post	6
trem_send_reward	8
trem_set_api_key	9
trem_ua	10

Index	11
--------------	-----------

trem_client_new	<i>Create a new Tremendous API Client</i>
-----------------	---

Description

Create a new Tremendous API Client

Usage

```
trem_client_new(api_key = NULL, sandbox = TRUE)
```

Arguments

api_key	API key from tremendous.com . Can either pass in here as a character string or set for repeated use with trem_set_api_key .
sandbox	Logical: TRUE and any API requests are performed within the Tremendous sandbox environment, a free and fully-featured environment for application developing and testing. FALSE and the API requests are performed within the Tremendous production environment. This will involve sending actual money, so be certain you wish to do this!

Value

An object of class 'tremClient' that contains the API Key and Environment information for easily performing Tremendous API requests.

Examples

```
## Not run:

# Create a client for testing API calls within the Sandbox environment.
test_client <- trem_client_new(api_key = "TEST_YOUR-KEY-HERE",
                              sandbox = TRUE)

# Create a client for performing API calls within a production environment.
# This client will be able to send actual money!
prod_client <- trem_client_new(api_key = "PROD_YOUR-KEY-HERE",
```

```
sandbox = FALSE)
```

```
## End(Not run)
```

```
trem_delete
```

```
Perform a DELETE request to Tremendous API
```

Description

Tremendous only supports DELETE requests for one endpoint – deleting an invoice. Per [their documentation](#), this request "removes an invoice. This has no further consequences but is a rather cosmetic operation." See the examples for a walk-through.

Usage

```
trem_delete(
  client,
  path,
  query = list(),
  body = NULL,
  disk = NULL,
  stream = NULL,
  encode = "json",
  parse = TRUE
)
```

Arguments

client	A Tremendous API Client object, created with trem_client_new .
path	The URL path, appended to the base URL, for GET requests such as listing available payment types, funding sources, account members, and more. See the Tremendous API Documentation for examples.
query	Query terms as a named list. See crul::HttpClient for more details.
body	Request body for Tremendous API, as an R List.
disk	A path to write to. NULL by default, so info is written to memory. See crul::HttpClient for more details.
stream	An R function to determine how to stream data. NULL by default, so info is streamed with memory. See crul::HttpClient for more details.
encode	"json" by default based on Tremendous API Request format. See crul::HttpClient for more options.
parse	Logical: Should the API Response results be parsed into a data frame?

Value

If parse = TRUE (default), a list containing the response from the API request. Otherwise, the R6 HttpResponseMessage object containing API request data.

Examples

```
## Not run:

# Create a new Tremendous API Client
test_client <- trem_client_new(api_key = "TEST_YOUR-API-KEY-HERE",
                              sandbox = TRUE)

# Perform a POST request for an invoice.
# `po_number` is Reference to the purchase order number within your organization
# `amount` is in USD
trem_post(test_client,
          path = "invoices",
          body = list(po_number = "unique-invoice-id",
                    amount = 50)
)

# Perform a GET request for listing all current (non-deleted) invoices.
current_invoices <- trem_get(test_client, "invoices")

# Get index for the correct ID
unique_id_index <- which(current_invoices$invoices$po_number == "unique-invoice-id")

# Get the invoice ID for 'unique-invoice-id' to delete
my_invoice_id <- current_invoices$invoices[unique_id_index, "id"]

# Perform a DELETE request for the specific invoice.
trem_delete(test_client, paste0("invoices/", my_invoice_id))

# Perform a GET request for listing all current (non-deleted) invoices.
# The one with id po_number 'unique-invoice-id' should no longer be here.
trem_get(test_client, "invoices")

## End(Not run)
```

trem_get

Perform a GET request to Tremendous API

Description

This function provides lower-level access to perform GET requests via Tremendous API. Available endpoints can be found on the official [Tremendous API documentation](#).

Usage

```
trem_get(  
  client,  
  path,  
  query = list(),  
  disk = NULL,  
  stream = NULL,  
  parse = TRUE  
)
```

Arguments

client	A Tremendous API Client object, created with trem_client_new .
path	The URL path, appended to the base URL, for GET requests such as listing available payment types, funding sources, account members, and more. See the Tremendous API Documentation for examples.
query	Query terms as a named list. See crul::HttpClient for more details.
disk	A path to write to. NULL by default, so info is written to memory. See crul::HttpClient for more details.
stream	An R function to determine how to stream data. NULL by default, so info is streamed with memory. See crul::HttpClient for more details.
parse	Logical: Should the API Response results be parsed into a data frame?

Value

If parse = TRUE (default), a list containing the response from the API request. Otherwise, the R6 `HttpResponse` object containing API request data.

Examples

```
## Not run:  
  
# Create a new Tremendous API Client  
test_client <- trem_client_new(api_key = "TEST_YOUR-API-KEY-HERE",  
  sandbox = TRUE) # Sandbox environment so no actual money is sent  
  
# Perform a GET request to list funding sources available in your Tremendous  
# Account. Documentation:  
# https://developers.tremendous.com/reference/core-funding-source-index  
trem_get(test_client, "funding_sources")  
  
# Perform a GET request to list all invoices on your Tremendous Account.  
# Documentation:  
# https://developers.tremendous.com/reference/core-invoices-index  
trem_get(test_client, "invoices")  
  
# Perform a GET request to list all orders (payment history) on your Tremendous  
# Account. Documentation:  
# https://developers.tremendous.com/reference/core-orders-index
```

```
trem_get(trem_client, "orders")

# Perform a GET request to list a specific order's information (payment history)
# from your Tremendous Account. Documentation:
# https://developers.tremendous.com/reference/core-orders-show
trem_get(trem_client, "orders/YOUR-ORDER-ID")

## End(Not run)
```

trem_post

Perform a POST request to Tremendous API

Description

This function provides lower-level access to perform POST requests via Tremendous API. Available endpoints can be found on the official [Tremendous API documentation](#).

For sending payments, I would recommend using [trem_send_reward](#) as it's more intuitive to use. However, this can be done using the `trem_post()` function (see examples).

Usage

```
trem_post(
  client,
  path,
  query = list(),
  body = NULL,
  disk = NULL,
  stream = NULL,
  encode = "json",
  parse = TRUE
)
```

Arguments

client	A Tremendous API Client object, created with trem_client_new .
path	The URL path, appended to the base URL, for GET requests such as listing available payment types, funding sources, account members, and more. See the Tremendous API Documentation for examples.
query	Query terms as a named list. See crul::HttpClient for more details.
body	Request body for Tremendous API, as an R List.
disk	A path to write to. NULL by default, so info is written to memory. See crul::HttpClient for more details.
stream	An R function to determine how to stream data. NULL by default, so info is streamed with memory. See crul::HttpClient for more details.

encode "json" by default based on Tremendous API Request format. See [crul::HttpClient](#) for more options.

parse Logical: Should the API Response results be parsed into a data frame?

Value

If parse = TRUE (default), a list containing the response from the API request. Otherwise, the R6 `HttpResponse` object containing API request data.

Examples

```
## Not run:

# Create a new Tremendous API Client
test_client <- trem_client_new(api_key = "TEST_YOUR-API-KEY-HERE",
                              sandbox = TRUE)

# Perform a POST request to invite new members to your Tremendous Account.
# Documentation: https://developers.tremendous.com/reference/post_members
trem_post(trem_client,
          path = "members",
          body = list(email = "example@website.com",
                     name = "Example Person",
                     role = "MEMBER"))

# Perform a POST send payments --
I find it ~tremendously~ easier to use the `trem_send_reward()` function.
# Documentation: https://developers.tremendous.com/reference/core-orders-create
trem_post(trem_client,
          path = "orders",
          body = list(
            external_id = "manual-payment-post", # This is a payment description id
            payment = list(
              funding_source_id = "your-funding-id-from-tremendous"
            ),
            rewards = list(
              value = list(
                denomination = 10,
                currency_code = "USD"
              ),
              delivery = list(
                method = "EMAIL" # "EMAIL", "LINK", or "PHONE",
              ),
              recipient = list(
                name = "first last",
                email = "email@website.com"
              ),
              # IDs for Applebee's Gift Card and Amazon Gift Card
              products = c("2JFKPXBWDC1K", "VW9JLMPRL9N7")
            )
          ))
```

```
## End(Not run)
```

trem_send_reward	<i>Send a Reward via Tremendous API</i>
------------------	---

Description

The most likely reason to use the tremendousr package is to send rewards. This function, `trem_send_reward()`, provides an easy interface to do so. See the examples for more details.

Usage

```
trem_send_reward(
  client,
  name,
  email = NULL,
  phone = NULL,
  reward_amount,
  currency_code = "USD",
  delivery_method = "EMAIL",
  payment_description_id,
  funding_source_id,
  reward_types,
  parse = TRUE
)
```

Arguments

<code>client</code>	A Tremendous API Client object, created with <code>trem_client_new</code> .
<code>name</code>	Name of the recipient.
<code>email</code>	Email address of the recipient.
<code>phone</code>	Phone number of the recipient (US phone numbers only).
<code>reward_amount</code>	Amount of the reward (numeric).
<code>currency_code</code>	Currency of the reward (default to "USD").
<code>delivery_method</code>	Default to "EMAIL", for sending the reward to the recipient via email. Alternatively, reward can be delivered via a link ("LINK") or text message ("PHONE").
<code>payment_description_id</code>	Unique ID for specific order. This will appear as <code>external_id</code> on Tremendous Dashboard.
<code>funding_source_id</code>	ID of the funding source linked to your account, to draw funds from for this order. One of the IDs from <code>trem_get("funding_sources")</code> .

reward_types A character vector of product ids – reward options – for the recipient to choose from. Available options can be found [here](#).

parse Logical: Should the API Response results be parsed into a data frame?

Value

If parse = TRUE (default), a list containing the response from payment API request. Otherwise, the R6 HttpResponse object containing API request data.

Examples

```
## Not run:

# Create a Tremendous Client
test_client <- trem_client_new(api_key = "TEST_YOUR-KEY-HERE",
                              sandbox = TRUE) # Sandbox environment so no actual money is sent

# To send a payment, you can simply pass in the client
# and specify the necessary fields.
payment1 <- trem_send_reward(client = test_client,
                             name = "first last",
                             email = "email@website.com",
                             reward_amount = 10,
                             currency_code = "USD",
                             delivery_method = "EMAIL",
                             payment_description_id = "payment-from-tremendousr-examples",
                             funding_source_id = "your-funding-id-from-tremendous",
                             reward_types = "Q24BD9EZ332JT", # ID for virtual visa gift card
                             parse = TRUE # Return a parsed API response
                           )

## End(Not run)
```

trem_set_api_key *Set Tremendous API Key in .Renviron*

Description

Set Tremendous API Key in .Renviron

Usage

```
trem_set_api_key(api_key)
```

Arguments

api_key API key from tremendous.com.

Value

NA; Used to set the Tremendous API key for persistent use in '.Renviron'.

Examples

```
if (interactive()) {  
  # For Sandbox Environment, your API key should look like:  
  trem_set_api_key("TEST_YOUR-API-KEY")  
  
  # For Production Environment, your API key should look like:  
  trem_set_api_key("PROD_YOUR-API-KEY")  
}
```

trem_ua

Get useragent info for tremendousr API Package

Description

Exported for use with [trem_client_new](#) to provide useragent info as a curl option for the API Request. This function was Adapted from [chimpr](#).

Usage

```
trem_ua()
```

Value

useragent info for tremendousr API Package

Examples

```
# Get useragent info for the tremendous API package  
trem_ua()
```

Index

`crul::HttpClient`, [3](#), [5–7](#)

`trem_client_new`, [2](#), [3](#), [5](#), [6](#), [8](#), [10](#)

`trem_delete`, [3](#)

`trem_get`, [4](#)

`trem_post`, [6](#)

`trem_send_reward`, [6](#), [8](#)

`trem_set_api_key`, [2](#), [9](#)

`trem_ua`, [10](#)